

Ground Maintenance, CE, Utility Tractors, Mowers, RTV's - 112624-KBA Ag Tractors with Related Attachments - 082923-KBA NJPA Arkansas 4600041718 Nebraska 14777 (OC) Mississippi 8200067336

KX033-4R3AE WEB QUOTE #2904172

Date: 8/19/2025 12:29:57 PM -- Customer Information --Broken Arrow, City of

67325 City of Broken Arrow bobo@tulsakubota.com 9182598361

Quote Provided By STEWART MARTIN KUBOTA OF **BROKEN ARR Bobo Newton** 1275 NORTH ELM PLACE **BROKEN ARROW, OK 74012** email: bobo@smekubota.com phone: 8706920458

Standard Features --

Kubata

K Series

KX033-4R3A

*** EQUIPMENT IN STANDARD MACHINE ***

FEATURES

Half Pitched Rubber Tracks or (Steel Tracks) ROPS/OPG (Top Guard, Level

4 Post Canopy or Heated Cab

with A/C

Suspension Seat Kubota 3 Hydraulic Pump Design

1 Gear, 2 Variable Displacement Pumps Hydraulic Joystick Controls with Wrist Rests Hydraulic Accumulator Two Operating Pattern Selection System Standard Front Dozer Blade 360 Degree Full Rotation 70° Left and 48° Right Boom

Swing Angle 15.8 GPM Adjustable Auxiliary Hydraulics Port

With Diverter Valve Five Second Quick Preheat System

Key Switch Stop System Self Bleed Fuel System Two Speed Travel

Auto Idle Thumb Bracket and Relief Valves

Swivel Negative Brake Travel Negative Brake Third Line Return (Hydraulic) **ENGINE**

Kubota D1703M-DI-E4 3 Cylinder, 4 Cycle 24.8 Gross HP (SAE J1995) @ 2200 RPM

23.2 Net HP (SAE J1349) @ 2200

OPERATIONAL DIMENSIONS Max Digging Depth 10' 6"

Max Digging Radius @ Ground Level 16' 10' Max Vertical Digging Depth 7' 4" Max Dumping Height 11' 7"

DOZER BLADE **DIMENSIONS**

Width 61" Height 13.5"/ 15.2"Angle Lift Above Ground 14.4"/

15.9"Angle Drop Below Ground 14.8"/

16.1"Angle

PERFORMANCE

Digging Force @ Bucket 8138 lbs Digging Force @ Dipper Arm 3867

Travel Speed (Low/High) 1.9/2.9 mph

Traction Force (Low) 6091 lbs Lift Capacity 3230 lbs

Over Front

Blade Grounded

2 Ft. Load Point Height

· 8 Ft. Load Radius

KX033-4R3AE Base Price: \$69,011.00 (1) BR360 Series Breaker, 1.65" tool dia. Width \$15,475.00 AP-BR510-01-21-BR360 Series Breaker, 1.65" tool dia. Width \$698.71 (1) EXCAVATOR (1) KEYLESS START KIT

- Custom Options -

77700-10659-EXCAVATOR (1) KEYLESS START KIT (1) CAB MIRROR KIT \$328.00

K7479-CAB MIRROR KIT \$1,467.00 (1) 12" QA TRENCHING BUCKET

K7872A-12" QA TRENCHING BUCKET

(1) QUICK COUPLER \$1,435,00 K7870A-QUICK COUPLER (1) 24" QA TRENCHING BUCKET \$1,986.00

K7875A-24" QA TRENCHING BUCKET \$461.00 (1) AT&T TELEMATICS MODEM

DCU6700-AT&T TELEMATICS MODEM (1) EXCAVATOR & WL TELEMATICS HARNESS \$167.00

K6704A-EXCAVATOR & WL TELEMATICS HARNESS \$91,028,71 Configured Price: (\$22,001.64)

Sourcewell Discount: \$69,027,07 SUBTOTAL:

2Yr KX033-4R3AE Extended Warranty \$2,200.00

\$372.17 Dealer Assembly: \$793.75 Freight Cost:

PDI: \$400.00

\$3,585.00 Hydraulic Quick Coupler with install

> Total Unit Price: \$76,377.99 **Quantity Ordered:**

Final Sales Price: \$76,377.99

Purchase Order Must Reflect Final Sales Price.

To order, place your Purchase Order directly with the quoting

DIMENSIONS AND OPERATING WEIGHT KX033-4R3AE Rubber Tracks, ROPS/OPG (Top Guard, Level 1) Cab, w/ Heat and A/C Angle Dozer Blade w/ bolt on cutting edge, Extendable Dipper Overall Length 15' 6"

Overall Width 5' 1" Overall Height 8' 1" Operating Weight* 7,742 lbs. Ground Clearance 11.4 *

Includes operator's weight. 175 lbs.

*All equipment specifications are as complete as possible as of the date on the quote. Additional attachments, options, or accessories may be added (or deleted) at the discounted price. All specifications and prices are subject to change. Taxes are not included. The PDI fees and freight for attachments and accessories quoted may have additional charges added by the delivering dealer. These charges will be billed separately. Prices for product quoted are good for 60 days from the date shown on the quote. All equipment as quoted is subject to availability.