CITY OF BROKEN ARROW RESOLUTION NO. 1637

ATTACHMENT A

Resolution to Request Programming of Tulsa Urbanized Area Surface Transportation Funds

WHEREAS, Surface Transportation Program Urbanized Area funds have been made available for transportation improvements within the Tulsa Transportation Management Area, and

WHEREAS, The City of Broken Arrow has selected a project described as follows: Widening of 23rd Street (193rd E. Ave.) to 5 lanes (4 lanes with a dedicated two-way left turn lane) from Albany Street (61st St. S.) to Omaha Street (51st St. S.), to include the replacement of the existing functionally obsolete 2-lane 23rd Street Bridge, NBI# 19345, with a 4-lane bridge structure, and the addition of a 5' sidewalk on the west side, and a 10' sidepath on the east side of 23rd Street; and

WHEREAS, the selected project is consistent with the local comprehensive plan, including applicable Major Street and Highway Plan Element, and the Regional Transportation Plan; and

WHEREAS, the engineer's preliminary estimate of cost is \$12,750,000.00, and Federal participation under the terms of the Surface Transportation Block Grant Program Urbanized Area funds are hereby requested for funding of 31.4 percent of the project cost; and

WHEREAS, the City of Broken Arrow proposes to use 2018 Streets General Obligation Bond funds for the balance of the project costs; and

WHEREAS, the City of Broken Arrow agrees to provide for satisfactory maintenance after completion, and to furnish the necessary right-of-way clear and unobstructed; and

WHEREAS, the City of Broken Arrow has required matching funds available and further agrees to deposit with the Oklahoma Department of Transportation said matching funds within the time frame as required by the ODOT.


NOW THEREFORE, BE IT RESOLVED: That the Indian Nations Council of Governments is hereby requested to program this project into the Transportation Improvement Program for the Tulsa Transportation Management Area; and should the project be selected for funding; and

BE IT FURTHER RESOLVED: That upon inclusion in the Transportation Improvement Program, the Oklahoma Transportation Commission is hereby requested to concur in the programming and selection of this project and to submit the same to the Federal Highway Administration for its approval.

	ATTEST:		
Mayor	Clerk		
(SEAL)	APPROVED AS TO FO	RM:	
	D. Graliam Parker	3/11/2025	
	Assistant City Attorney		

CITY OF BROKEN ARROW - PRIORITY NO. 1 PROJECT

Attachment B - Tulsa Transportation Management Area



Attachment C - Tulsa Urban Area Surface Transportation Program Project **Rating Form**

A. Application Information

Project Title	ST1931 & ST1932 - 23rd St. Widening from Albany to Omaha
Project Location	193rd E Ave. (County Line Rd.) from 61st St. S. to 51st St. S.
Sponsor	City of Broken Arrow
Sponsor Contact Name	Brent Stout
Sponsor Contact Title	Transportation Project Manager
Address	485 North Poplar Ave, Broken Arrow, OK 74012
Phone	(918) 259-7000 Ext. 7395
Email	bstout@brokenarrowok.gov

B. Project Financial Information – Include a detailed, complete, realistic cost estimate, and summarize below:

PROJECT BUDGET							
			Percent		Federal Funds	Sponsor Funds (20% Minimum)	TOTAL
Pre-Construction Costs:							
Planning/Design							
ROW							
Utility Relocation							
Sub-total							
Construction Cost					\$3,120,000	\$6,800,000	\$9,920,000
Contingency Cost (%)			_10_%		\$310,000	\$680,000	\$990,000
Sub-total			_		\$3,430,000	\$7,480,000	\$10,910,000
Escalation	# of yrs_2	<u>5</u> % per yr	10.3 %		\$350,000	\$770,000	\$1,120,000
Sub-total					\$3,780,000	\$8,250,000	\$12,030,000
Construction Management & Inspection (%)				6%	\$220,000	\$500,000	\$720,000
TOTAL					\$4,000,000	\$8,750,000*	\$12,750,000

Note: In the application, please provide (a) The source of cost estimates and attach the most detailed and complete cost estimate available. Annual cost escalation to year of expenditure percentage and Construction Management & Inspection fee is provided as guidance but you may use the best applicable percentages to your project provided you have a basis. Total Federal Funds are capped for the project once awarded.

⁻ Only City of Broken Arrow funds used for planning/engineering design, right-of-way acquisition and utility relocation.

* \$3 mil of this total amount has already been allocated funding to City of Broken Arrow from a previous STP application.

\$3.0 million in Surface Transportation Program (STP) funds has previously been awarded and allocated to this project for the City of Broken Arrow. With this application, the City of Broken Arrow hopes to accomplish fully funding this project to construct a 5-lane arterial roadway in accordance with the INCOG Major Street and Highway Plan. The cost estimate of this project is \$12.75 million and with the full award of funding for this application, there should be sufficient funding to construct the project as designed.

- 1) Applicants are required to include a minimum of **6%** Construction Management & Inspection costs per ODOT's recommendation.
- 2) Projects selected often take two years or more for preconstruction activity before they are ready for letting. The local project sponsor must provide an annual cost escalation to the year of expenditure.
- 3) All federal funds will be capped for awarded projects inclusive of CM&I fees.

,	• • • • • • • • • • • • • • • • • • • •	. ,			
Certification	n:				
the legal aut	hority to pledge matching t s. I further certify that matc	funds, and has	the legal		ate or
Signature:	Charlie Bright		Date:	3/12/25	
Printed Nam	Charlie Bright		Title:	Engineering Director	

A. Travel Time Improvement - Maximum 30 Points

Projects that seek to improve travel time can receive up to 30 points in this category. Improvements are usually in the form of capacity addition or intersection improvements.

1.	What is the most recent average daily traffic count for the proposed project location? (For new alignments the projected volume and number of lanes from the most current computer model of the long-range transportation plan will be used. For intersection improvements, traffic volume of all approaches averaged will be used to determine the V/C ratio.)
	Count: 13,963 Date: 3/12/25
	Future Forecasted Traffic Volumes (2050):34,042
	Current number of lanes: 2 Count per lane: 6,982
exist	corridor improvements, INCOG will determine if the proposed project provides relief for an ing/future congested corridor location, using volume to capacity (V/C) ratio where Level of ice C capacity is greater than 0.80.
	V/C Ratio 1.50 of greater (18 points) V/C Ratio 1.20 or greater (12 points) V/C Ratio 1.00 to 1.19 (8 points) V/C Ratio 0.80 to 0.99 (4 points) V/C Ratio less than 0.80 (0 points)

- Cost Points: Max 6 Points INCOG will calculate the STBG dollar cost per daily traffic volume. The projects will be divided into quartiles and the first quartile will receive 6 points, the second quartile 4 points, the third quartile 2 points and the fourth quartile 1 point.
- If the project is exclusively related to intersection improvements: Additional 6 Points (Example: for Traffic Flow Improvements such as Arterial intersection projects, System
 Management/Integration, Turning Movement improvements, adding turn lanes to existing roadway or other related corridor traffic improvement projects that include intersection improvements to reduce congestion) –

Please provide any additional comments on congestion improvements:

Widening from 2 lanes to 5 lanes (with continuous 2-way left turn lane) for improving left turn movements which will provide relief from future congestion due to residential/commuter traffic as well as heavy vehicles (existing commercial vehicles and public school buses). This corridor is moderately utilized by heavy vehicles to transport goods to the Port of Catoosa and will continue to experience both residential and commercial development in the near term. There has been recent high density residential development on the corridor. The center turn lane will lessen the impacts of increased future traffic volumes on congestion greatly. The intersection of 23rd Street and Albany Street will also be improved/widened. Tulsa County is improving the intersection of 23rd and Omaha Street with the construction of a roundabout, abutting the northern project limits of this potential project.

B. Safety Improvements - Maximum 30 Points

If the project is designed to mitigate identified safety issues, it can receive up to 30 points in this category. Please provide a description in the space provided next to each applicable criterion.

What is the Average Annual Crash Severity Index for the Project? _____(INCOG will calculate based on data from DPS/ODOT related to Fatality, Injury & PDO crashes)

First Quartile of Projects: 18 Points
Second Quartile of Projects: 12 Points
Third Quartile of Projects submitted: 8 Points
Fourth Quartile of Projects submitted: 4 Points

If the project is not an EXCLUSIVE safety project, it may not receive above points, but eligible to receive following points:

Evaluation Criteria	Points	Provide Description
Project includes transit, pedestrian, bicycle & wheelchair traffic safety. Ex: signalized crossings, high visibility markings, signage, crosswalk upgrades, sidewalk extensions, pedestrian ramps, lighting, barriers separating vehicle/person conflicts. (List each item that is a part of the design separately to receive 1 point each, up to 4 points total.)	4	Upgrades/Improvements include: Pedestrian crosswalks, pavement markings, new signage, addition of 5' sidewalk and 10' sidepath for the entire length of the project, addition of curb & gutter to provide a barrier between traffic and pedestrians on sidewalk/trail, widening from 2-lanes to 5 lanes (with continuous 2-way left turn lane) from Albany to Omaha for improving left turn movements for BAPS bus routes in the vicinity, and other heavy vehicles utilizing this street.
Projects to improve roadway safety and/or address Traffic Incident Management. Ex: pavement markings, lighting, signage, barriers or increase skid resistance, responder safety, equipment, communication systems, design features such as incident detection/synchronized signals, turning lane improvements, super-two-lane configuration with added shoulders (List each item that is a part of the design separately to receive 1 point each, up to 4 points total.)	4	Upgrades/improvements include: Pedestrian crosswalks, pavement markings, new signage, addition of a continuous left turn lane on 23rd from Albany to Omaha, provides better access for emergency responders and gives additional roadway for clearing traffic incidents. New pavement/ overlay will provide better skid resistance.
Project increases safety through rail crossing improvements.	4	
TOTAL		

Comments:

This project will reduce the number and severity of collisions being reported on this segment of 23rd Street. The addition of capacity by the addition of a center turn lane will provide for safer turning movements on the corridor. Safety will be improved and the number of accidents will be reduced by the addition of sidewalks, curb ramps, visible signals, crosswalks, lighting, signing, striping and pedestrian signals. Curve realignment (horizontal and vertical) of the roadway geometrics in the area of the reconstructed bridge for improved sight distance and reduced risk of head-on collisions will be accomplished with this project.

Arterial intersection related safety criteria:

Additional points will be awarded for projects that are proposed to improve unsafe intersections, railroad crossings and/or bridges Using the ODOT Public Safety data from the past three years, INCOG will calculate the most recent average annual crash count at the proposed project location:

Number of Crashes: 1	4*	Date:	2022-2024
Crash Severity Index:			
Points Awarded:			

The projects will be divided into quartiles based on the Crash Severity Index and the first quartile will receive 2 points, the second quartile 4 points, the third quartile 6 points and the fourth quartile 8 points. Projects that involve rehabilitation of existing facilities only, with no targeted additional safety features/improvements, are not eligible for "Crash Severity" points.

* 14 total crashes - 1 with serious injury, and 4 with minor injuries.	
--	--

C. System Maintenance and Management – Maximum 30 Points

If the <u>main purpose of the proposed project is to maintain, rehabilitate or rebuild existing</u> <u>facilities</u>, it may receive up to 30 points in this category. Please provide a description in the space provided next to each applicable criterion.

Evaluation Criteria	Points	Provide Description
Project includes either resurfacing or rehabilitation of a majority of the extent, substantial drainage improvements.	15	Utilization of existing pavement by rehab, via patching/mill/overlay. 2) Replaces existing inadequate ditches with ditch improvements, enclosed storm sewers, improved cross drains and bridge replacement.
Project improves signalization and/or aids in the detection and clearance of non-recurring traffic incidents, the rapid clearing of road obstructions, or otherwise contributes to or utilizes ITS technology or incident management elements.	15	This project connects to Tulsa County improvements at the intersection of 23rd and Omaha, which converts a signalized intersection to a roundabout. Additional width and a two-way left turn lane will be included in the project, which will assist in clearing of traffic incidents and/or obstructions in the roadway.
Project is derived from or related to the INCOG Congestion Management Process and reduces congestion on streets or intersections functionally classified by the FHWA as arterials in incorporated areas or as a major rural collectors in unincorporated areas.	5	Project widens 23rd Street (an arterial street) by adding two lanes and a two-way continuous left turn lane allowing better turning movements thereby decreasing congestion.
TOTAL		

Comments:

This project will rehabilitate the existing pavement, and widen the roadway with the addition of new pavement for the outside lanes. There will be a center turn lane added to this arterial mile project as well. This project ties into the recently completed reconstruction of the 23rd Street and Albany Street intersection.

D. Livability Criteria - Maximum 30 Points

If the <u>main purpose of the proposed project is transit components, pedestrian components, or bicycle components</u>, it may receive up to 30 points in this category. If the project is NOT an alternative-mode enhancement, but it includes design considerations for the operation thereof, it may obtain up to 15 points. Please provide a description in the space provided next to each applicable criterion.

Evaluation Criteria	Points	Provide Description
The project is a transit facility improvement, pedestrian or bicycle facility per the GO plan	30	This project includes the addition of a 5' sidewalk on the west side, and a 10' sidepath on the east side of 23rd Street.
If main purpose of project is complementary features, plant		ative mode, but it does include bellow.
Project provides for existing or planned bus/transit/school bus operations (<i>i.e.</i> , turning radii, bus stop pad, etc)	5	23rd Stret et heavilla wird by EARS BIASH Set hool Widening will provide safer facility for these yehicles (width, puses of the serve o
Project provides for pedestrian or bicycle components (bump outs, sidewalks, shelters, wide shoulders, dedicated lanes, paths/trails etc)	5	This project will add a 5' sidewalk and a 10' trail (no continuous sidewalks currently exist for the full length of the the project). ADA curb ramps and crosswalks with pedestrian safety measures will be added.
Project (<u>not</u> a limited access facility) is primarily located in a district zoned as Commercial, Office, High-Density Single-Family Residential, or Medium-Density Multi-Family.	5	This project is located through an area with significant numbers of high density housing units (apartments) and single family residential housing. The arterial is also a route heavily utilized by commercial traffic due to connections to highways and Port of Catoosa as well as other businesses in the area.
Project displaces one or more homes, businesses, schools, churches or recreational areas.	-10	No Displacements are required for this project.
TOTAL		

Comments:

This project includes a 5' sidewalk on the west side of 23rd, and a 10' multi-use trail on the east side for the full length of the project that will be used primarily by pedestrians and bicyclists. It is anticipated that these facilities will be utilized frequently, as there are apartment complexes and numerous single family residences along the corridor, which lead to the largest high school in the state of Oklahoma. These facilities will be designed to be fully ADA-compliant.

E. Freight Movement and Intermodal Linkages – Maximum 20 Points

If the project induces the interaction between two or more modes of transportation, it may receive up to 20 points in this category. Please provide a description in the space provided next to each applicable criterion.

Evaluation Criteria	Points	Provide Description
Project facilitates the exchange of passengers and/or goods from private to public modes or between transportation modes.	10	23rd Street is heavily used by BAPS school buses and is a significant route for heavy vehicles of various uses due to route for Port of Catoosa and due to the connection to highways in the area.
Project improves access to existing or proposed transportation freight or passenger terminal facility	10	23rd Street is a heavily traveled rote transporting goods due to the connection to highways between Broken Arrow, Catoosa, and Coweta as well as the Port of Catoosa. 23rd Street is heavily used by public school buses.
Project improves road component(s) with 5% or more heavy duty trucks by traffic volume substantiated with observed vehicle classification data as an attachment	10	+5% Heavy vehicles utilize the 23rd Street corridor due to businesses in the area. Heavy vehicles transport goods along the corridor because of connections to highway systems in the area as well as the Port of Catoosa.
TOTAL		

Comments:

Because this corridor is heavily used by Broken Arrow Public Schools school buses, this is a point of interaction between pedestrians and transit users. The addition of 3-lanes including a center turn lane will make travel safer and more convenient for large trucks using the corridor to get to and from the Port of Catoosa.

F. Project Preparation – Maximum 20 Points

Projects that are prepared for construction may receive up to 20 points in this category. Please provide a description in the space provided next to each applicable criterion. Additionally, INCOG may reduce the project score if previously awarded projects are not advancing to construction in a timely manner unless circumstances are out of the applicant's control.

	Pt	Provide Description
What is the status of the environmental revie	ew prod	cess?
Environmental clearance completed and	5	
federal approval obtained.		
Safety and/or Active Transportation Projects	3	
that are deemed to be a CE projects		
Environmental clearance is in process in	1	Initial Environmental work has begun
compliance with federal requirements		for consultation with the USACOE.
Environmental clearance has not been	0	
initiated		
EIS likely to be required	-4	
What is the status of proposed project design	n/ engi	neering/ planning?
Final Design/ Engineering/ planning	10	Final design plans have been submitted
completed and approved by ODOT.		to ODOT and are under review.
Preliminary Design/ Engineering 60% plans	6	
completed.		
Preliminary Design/ Engineering/ Planning	2	
design consultant selected.		
What is the status of right-of-way acquisition		
Right-of-way acquisition completed or not	5	Right-of-way acquisition to be
required per ODOT approved plans.		complete by March 2025.
Right-of-way acquisition based on area is 50%	2	
complete in compliance with federal		
requirements		
Right-of-way acquisition has not been initiated	0	
What is the status of utility relocation?		
Utility relocation plans are completed or not	5	Utility plans are complete and
required per ODOT approved plans.		relocation is in progress.
Utility relocation is 50% complete in	3	
compliance with federal requirements		
Utility relocation has not been initiated	0	
What is the amount of matching funds for S1	TBG Fι	unds?
More than 50% (6pts), 25 – 50% (4pts)	4 or	COBA funds will cover approximately
	6	45.1% of project cost.
TOTAL		

G. Multijurisdictional Projects – Maximum 20 Points

Multijurisdictional transportation projects are transportation projects that can involve multiple jurisdictions, such as cities, counties, states, and/or the federal government. These projects can improve safety, efficiency, and reliability for people and goods. Please provide a description in the space provided next to each applicable criterion.

Evaluation Criteria	Points	Provide Description
Project is multi-jurisdictional and is a part of a regional funding program or economic development or Travel/Tourism strategy that benefits more than one community and/or county involving multiple local public agencies.	10	23rd Street is heavily traveled by commuters of Broken Arrow, Coweta, Tulsa and Catoosa (as well as Tulsa, Rogers & Wagoner County Residents). The route is also significant due to the economic benefit of the businesses (goods & transportation) along the corridor and connections to highways in the area and the Port of Catoosa. This segment of 23rd Street bridges both Tulsa and Wagoner Counties and is a route into Rogers County.
Project involves multiple partners that participate with substantial local match in funding, greater than 25% of total match required, substantiated with a letter of commitment from the partner(s).	10	
TOTAL		

Comments:

This project benefits users in multiple communities and counties in northeast Oklahoma. It connects to area highways and provides access to the Port of Catoosa, the furthest inland port facility in the United States.

H. Regional Priorities – Maximum 20 Points

Please describe the extent to which the proposed project offers significant additional benefits to the region in terms of functionally obsolete or structurally deficient bridges and/or projects on boundary roads that are shared between two or more jurisdictions. Please provide a description in the space provided next to each applicable criterion.

Evaluation Criteria	Points	Provide Description
Project includes replacement or rehabilitation of a functionally obsolete or structurally deficient bridge, such that it no longer is a functionally obsolete or structurally deficient.	10	Project includes the replacement of a functionally obsolete bridge with a sufficiency rating of 47.5 with a new bridge, sufficiently wide enough to accommodate 4-lanes of traffic.
Projects involving boundary roads between two or more jurisdictions.	10	23rd Street is also County Line Road which is the boundary between Tulsa County and Wagoner County.
TOTAL		

Comments:

23rd Street, also known as 193rd E. Ave. or County Line Road, is the boundary between Tulsa County and Wagoner County. This project ties in to the Tulsa County roundabout project at 23rd and Albany. It is utilized by citizens of both counties to access highways and businesses along the corridor.

Letting: Call Order: Contract ID:



Oklahoma Department of Transportation Detail Cost Estimate

Project ID: 36448(04)

Project Description: 23rd STREET (193rd E. AVE.)

Spec Book: 19

Date Printed: 12/12/2024

Federal Project Number: 36448(04)



Detail Estimate Cost Summary

Page 1 of 1

Project Description: 23rd STREET (193rd E. AVE.) Project ID:3644804

Funding **Funding Limit** Total E&C Amount Total Fund Package Cost **Fund Package**



Page 1 of 12

Project ID: 3644804 Federal Project Number: 36448(04)

Project Description: 23rd STREET (193rd E. AVE.)

	Flags*
Fund	Package ID
	ext. Amount
	Ш
	Price
	Qty.
	"
	Units
Alt.	Member Units
	Member
	n Set Member I

Alternate Member Alternate Set ROADWAY Category 0100 Funding Source(s) and Participation: Multiple Fund Packages exist for the Category. See other Funding reports for details.

Fed Work Class:

Fed Construction Class:

Category Length: 0
Category Width: 0

	Category	Category Work Class:				Category Width: 0	
0010	201(A)1200	CLEARING AND GRUBBING	RSUM	1.000	175,000.00000	175,000.00	L B
0020	202(A)2200	UNCLASSIFIED EXCAVATION	CY	25,289.000	11.00000	278,179.00	_
0030	202(D)2500	UNCLASSIFIED BORROW	CY	2,053.000	16.00000	32,848.00	_
0040	205(A)6200	TYPE A-SALVAGED TOPSOIL	RSUM	1.000	75,000.00000	75,000.00	LB
0020	221(B)2300	TEMPORARY SILT FENCE	H	3,522.000	3.50000	12,327.00	_
0900	221(C)2400	TEMPORARY SEDIMENT FILTER	EA	34.000	300.0000	10,200.00	_
0000	221(E)2600	TEMPORARY SILT DIKE	F	217.000	18.00000	3,906.00	_
0080	221(F)2720	TEMPORARY ROCK FILTER DAM TYPE 3	ζ	37.000	200.00000	7,400.00	_
0600	230(A)7200	SOLID SLAB SODDING	SY	15,515.000	4.00000	62,060.00	L
0100	303(A)1200	AGGREGATE BASE TYPE A	C	8,396.000	76.00000	638,096.00	L
0110	310(B)5300	SUBGRADE, METHOD B	SY	39,775.000	3.00000	119,325.00	L
0120	325 0100	SEPARATOR FABRIC	SY	32,986.000	2.00000	65,972.00	L
0130	411(B)1330	SUPERPAVE, TYPE S3(PG 64-22 OK)	NOT	13,538.000	110.00000	1,489,180.00	_



Page 2 of 12

Project ID: 3644804 Federal Project Number: 36448(04)



Page 3 of 12

Project ID: 3644804 Federal Project Number: 36448(04)

•	-	•	,						
Line #	Ref. ID	Description	Alt. Alt. Set Member	Units	Qty.	Price	Ext. Amount	Fund Package ID	Flags*
1	/ ->	DIA.)		÷					,
0330	611(B)7321	(PL) ADD'L.DEPTH IN MANHOLE (8' DIA.)		٧F	10.000	750.00000	7,500.00		_
0340	611(G)0104	INLET W/LRG. JCT. BOX, CI, DES 1(A)		EA	000'9	7,500.00000	45,000.00		ı
0320	611(G)0144	INLET W/LRG. JCT. BOX, CI, DES.2		EA	2.000	9,000.00000	18,000.00		_
0360	611(G)0148	INLET W/LRG. JCT. BOX, CI, DES.2(B)		EA	1.000	11,500.00000	11,500.00		_
0370	611(G)0172	INLET W/LRG JCT BOX, CI, DES.3		EA	8.000	11,500.00000	92,000.00		
0380	611(G)0224	INLET W/SMALL JCT. BOX, CI, DES. 1(A)		EA	5.000	7,000.00000	35,000.00		_
0380	611(G)0304	INLET W/SMALL JCT. BOX, CI, DES.3		EA	3.000	11,800.00000	35,400.00		_
0400	611(G)7754	INLET CI DES. 2 (STD)		EA	1.000	5,800.00000	5,800.00		_
0410	611(G)7766	INLET CI DES. 2 (D)		EA	1.000	7,900.00000	7,900.00		_
0420	611(G)9000	INLET CDI RCP DES. 1		EA	5.000	4,725.00000	23,625.00		_
0430	611(H)0784	ADD'L DEPTH IN INLET W/LJB, CI, DES. 1(A)		VF	17.000	300.00000	5,100.00		_
0440	611(H)0820	ADD'L DEPTH IN INLET W/LJB, CI, DES. 2		٧F	3.000	500.00000	1,500.00		
0450	611(H)0824	ADD'L DEPTH IN INLET W/LJB, CI, DES. 2(B)		VF	3.000	500.00000	1,500.00		
0460	611(H)0844	ADD'L DEPTH IN INLET W/LJB, CI, DES. 3		VF	29.000	700.00000	20,300.00		_
0470	611(H)0884	ADD'L DEPTH IN INLET W/SJB, CI, DES. 1(A)		VF	10.000	300.00000	3,000.00		_
0480	611(H)0944	ADD'L DEPTH IN INLET W/SJB, CI, DES. 3		VF	7.000	1,100.00000	7,700.00		-1
0490	611(L)1600	JUNCTION BOXES		CF	230.000	135.00000	31,050.00		_



Page 4 of 12

Project ID: 3644804 Federal Project Number: 36448(04)

7					
1,920.00	1,920.00 13,740.00 733,096.00 1,500.00 1,653.00	1,920.00 13,740.00 733,096.00 1,500.00 115,581.00 86,475.00	1,920.00 13,740.00 733,096.00 1,500.00 115,581.00 86,475.00 165,490.00 6,820.00 84,320.00	1,920.00 13,740.00 733,096.00 1,653.00 115,581.00 86,475.00 6,820.00 6,820.00 1,720.00 1,720.00	1,920.00 13,740.00 733,096.00 1,550.00 1,15,581.00 86,475.00 6,820.00 6,820.00 1,720.00 1,720.00 22,830.00 7,311.00
640.00000	640.00000 6,870.00000 424.00000 150.00000 57.00000	640.00000 6,870.00000 424.00000 150.00000 57.00000 75.00000	640.00000 6,870.00000 150.00000 57.00000 75.00000 134.00000 170.00000 170.00000	640.00000 6,870.00000 150.00000 57.00000 75.00000 134.00000 170.00000 940.00000 50,000.00000	640.00000 6,870.00000 150.00000 57.00000 75.00000 174.00000 1,720.00000 50,000.00000 1,522.00000 3.00000
3.000	3.000 2.000 1,729.000 10.000 29.000 1,959.000	3.000 2.000 1,729.000 1,959.000 1,153.000	3.000 2.000 1,729.000 1,959.000 1,153.000 1,235.000 55.000 496.000	3.000 2.000 1,729.000 1,959.000 1,153.000 1,235.000 55.000 2.000 1.000	3.000 2.000 1,729.000 1,959.000 1,153.000 1,235.000 55.000 496.000 1.000 1.000 1.000 1.000 2.437.000
Š	{	{	{	EA E E E E E A E E E E E E E E E E E E	E A SUM
	FIRE HYDRANT RESET 54" R.C.PIPE CLASS III 18" X 18" R.C.PIPE ARCH CLASS A-III 15" CORRUGATED 19" CORRUGATED 10" CORRUGATED 10" CORRUGATED 10" CORRUGATED	ANT RESET E CLASS III C.PIPE ARCH CLASS A-III GATED YLENE PIPE	FIRE HYDRANT RESET 24" R.C.PIPE CLASS III 15" CORRUGATED POLYPROPYLENE PIPE 18" CORRUGATED POLYPROPYLENE PIPE 24" CORRUGATED POLYPROPYLENE PIPE 30" CORRUGATED POLYPROPYLENE PIPE 30" CORRUGATED POLYPROPYLENE PIPE 30" CORRUGATED POLYPROPYLENE PIPE 36" CORRUGATED POLYPROPYLENE PIPE 18" CORRUGATED POLYPROPYLENE PIPE 18" FEFAB. CULVERT END SEC., ROUND	FIRE HYDRANT RESET 54" R.C.PIPE CLASS III 15" CORRUGATED POLYPROPYLENE PIPE 18" CORRUGATED POLYPROPYLENE PIPE 24" CORRUGATED POLYPROPYLENE PIPE 30" CORRUGATED POLYPROPYLENE PIPE 30" CORRUGATED POLYPROPYLENE PIPE 30" CORRUGATED POLYPROPYLENE PIPE 30" CORRUGATED POLYPROPYLENE PIPE 16" FREFAB. CULVERT END SEC., ROUND 30" PREFAB. CULVERT END SEC., ROUND 30" PREFAB. CULVERT END SEC., ROUND 30" PREFAB. CULVERT END SEC., ROUND SO" PREFAB. CULVERT END SEC., ROUND REMOVAL OF STRUCTURES & OBSTRUCTIONS	ANT RESET E CLASS III C.PIPE ARCH CLASS A-III GATED YLENE PIPE
612(G)3800 FIRE HYDRANT RESET	613(A)5236 54" R.C.PIPE CLASS III 613(A)5358 28" X 18" R.C.PIPE ARCH 613(EE)5965 15" CORRUGATED POLYPROPYLENE PIPE 613(EE)5969 18" CORRUGATED				
					0550 613(A)5250 0550 613(E)596 0570 613(E)596 0580 613(E)597 0600 613(E)598 0610 613(E)598 0620 613(E)598 0630 613(B)6300 0650 619(B)6350



Page 5 of 12

Project ID: 3644804 Federal Project Number: 36448(04)

			·						
Line #	Ref. ID) Description	Alt. Alt. Set Memb	Alt. Member Units	Qty.	Price	Ext. Amount	Fund Package ID	Flags*
0890	619(B)6360	REMOVAL OF CONCRETE PAVEMENT		λS	32.000	19.00000	608.00		
0690	619(B)6364	REMOVAL OF ASPHALT PAVEMENT		SY	8,663.000	000006	77,967.00		_
0200	619(B)6368	REMOVAL OF DRAINAGE INLETS		EA	2.000	1,350.00000	2,700.00		_
0710	619(B)6372	REMOVAL OF MANHOLES		EA	2.000	900.00000	1,800.00		_
0720	619(B)6380	REMOVAL OF CONCRETE DRIVEWAY		λS	982.000	16.00000	15,712.00		_
0230	619(B)6384	REMOVAL OF ASPHALT DRIVEWAY		SY	1,173.000	10.00000	11,730.00		_
0740	619(B)6396	REMOVAL OF GUARDRAIL		님	1,471.000	000000	8,826.00		_
0220	619(B)6404	REMOVAL OF SIDEWALK		SY	149.000	20.00000	2,980.00		_
0920	619(B)6420	REMOVAL OF RIPRAP		S	1,082.000	4.00000	4,328.00		_
0770	619(B)6440	REMOVAL OF EXISTING PIPE		I.F	000.089	13.00000	8,840.00		7
0280	619(C)6600	SAWING PAVEMENT		H	1,582.000	4.00000	6,328.00		_
0620	624 3100	(PL) ORNAMENTAL FENCE		님	114.000	230.00000	26,220.00		_
0800	624(C)3400	FENCE-STYLE SWF (4 BARBED WIRE)		느	120.000	12.00000	1,440.00		_
0810	624(C)3405	FENCE-STYLE SWF (5 BARBED WIRE)		片	485.000	14.00000	6,790.00		_
0820	624(E)3600	FENCE-STYLE CLF (4'HIGH, CLASS A)		느	219.000	00000	14,235.00		_
0830	624(E)3625	FENCE-STYLE CLF (6'HIGH, CLASS B)		띰	357.000	44.00000	15,708.00		_
0840	624(H)3900	(PL) GATE		EA	1.000	1,620.00000	1,620.00		_
0820	629(A)7200	MAILBOX INSTALLATION-SINGLE		EA	5.000	270.00000	1,350.00		_



Page 6 of 12

Project ID: 3644804 Federal Project Number: 36448(04)

Project Description: 23rd STREET (193rd E. AVE.)

Line	<u> </u>		Alt.	Alt. Alt.		į	; ;	4	Fund	į
#	# Ker. ID	Description	Set	Member	Onits	ָבָּוּלַ. יַ	Fice	Ext. Amount	Package ID	Flags
0860	629(C)7400	REMOVAL OF MAILBOX INSTALLATION			EA	5.000	150.00000	750.00		_
0870	629(E)7600	MAILBOX			EA	5.000	155.00000	775.00		7
						Category Total		\$6 293 780 00		

Alternate Member Alternate Set WATERLINE Category 0110 Funding Source(s) and Participation: Multiple Fund Packages exist for the Category. See other Funding reports for details.

Category Length: 0

Fed Work Class:

Fed Construction Class:

Category Width: 0 Category Work Class:

_	7	7	_	_	_	_	_	_
9,648.00	30,380.00	219.00	4,210.00	00.009	3,300.00	7,100.00	9,600.00	8,100.00
36.00000	245.00000	73.00000	4,210.00000	200.00000	1,100.00000	1,775.00000	1,200.00000	900.0000
268.000	124.000	3.000	1.000	3.000	3.000	4.000	8.000	000'6
5	4	Ħ	EA	EA	EA	EA	EA	EA
4" POLYVINYL CHLORIDE (PVC) PIPE	12" POLYVINYL CHLORIDE (PVC) PIPE	3/4" COPPER WATER SERVICE PIPE	2" COMB.AIR RELEASE ASSEMBLY AND VAULT	3/4" CORPORATION STOPS	4" SOLID SLEEVE	12" SOLID SLEEVE	12" 45 DEGREE FITTING	4" 45 DEGREE BEND
616(B)2332	616(B)2352	616(C)2400	616(D)2538	616(E)2900	616(K)3508	616(K)3524	616(O)4045	616(Q)4205
0880	0880	0060	0910	0920	0860	0940	0920	0960

\$73,157.00

Category Total:



Page 7 of 12

Project ID: 3644804 Federal Project Number: 36448(04)

Project Description: 23rd STREET (193rd E. AVE.)

	Flags*
Fund	Package ID
	Ext. Amount
	Price
	Qfy.
	Units
Alt.	Member
Alt.	Set
	Description
	Ref. ID
Line	#

Alternate Member Alternate Set WASTEWATER Category 0120 Funding Source(s) and Participation: Multiple Fund Packages exist for the Category. See other Funding reports for details.

Fed Work Class:

Category Length: 0 Category Width: 0 Fed Construction Class:

Category Work Class:

_	7	_	L	
0	0	0	0	0
19,500.00	3,500.00	00'000'66	6,400.00	\$128,400.00
6,500.00000	200.0000	200.00000	320.00000	Category Total:
3.000	7.000	495.000	20.000	Categor
EA	٩	片	4	
(PL) MANHOLE (4' DIA.)	(PL) ADD'L.DEPTH IN MANHOLE (4' DIA.)	10" POLYVINYL CHLORIDE (PVC) PIPE	20" STEEL CASING	
611(A)7211	611(B)7301	615(A)1224	616(1)3330	
0260	0860	0660	1000	

Alternate Member Alternate Set **BRIDGE A** Category 0200

Multiple Fund Packages exist for the Category. See other Funding reports for details. Funding Source(s) and Participation:

Fed Work Class:

Fed Construction Class:

Category Length: 0
Category Width: 0

Category Work Class:

1010

3.720.00 31.00000 120.000 ζ SUBSTRUCTURE EXCAVATION 501(B)1300



Page 8 of 12

Project ID: 3644804 Federal Project Number: 36448(04)

##	Ref. ID	Description	Alt. Alt. Set Member	Units	Qty.	Price	Ext. Amount	Fund Package ID	Flags*
	/ _ /	COMMON))) 1))))			
1020	501(G)1800	CLSM BACKFILL		ς	321.100	240.00000	77,064.00		_
1030	502 3100	TEMPORARY EARTH RETAINAGE		LSUM	1.000	75,000.00000	75,000.00		L B
1040	503(A)4240	PRESTRESSED CONCRETE BEAMS (TYPE IV)		F.	1,284.500	345.00000	443,152.50		_
1050	504(A)5200	APPROACH SLAB		SY	347.600	265.00000	92,114.00		_
1060	504(D)5420	CONCRETE RAIL (TR4)		FJ.	466.000	130.00000	60,580.00		_
1070	504(F)5600	HANDRAILING		F	466.000	180.00000	83,880.00		_
1080	506(A)7200	STRUCTURAL STEEL		LB	1,840.000	5.25000	00.099,6		_
1090	507(A)8210	WEATHERING STEEL FIXED BEARING ASSEMBLY		EA	14.000	1,800.00000	25,200.00		_
1100	507(B)8300	STAINLESS STEEL EXP. BEARING ASSEMBLY		EA	28.000	2,900.00000	81,200.00		_
1110	507(C)8400	ELASTOMERIC BEARING PADS		EA	28.000	350.00000	9,800.00		Γ
1120	509(A)0210	CLASS AA CONCRETE		ς	512.000	905.00000	463,360.00		7
1130	509(B)0320	CLASS A CONCRETE		CY	256.600	880.00000	225,808.00		_
1140	511 2100	MECHANICAL SPLICES		EA	1,394.000	45.00000	62,730.00		_
1150	511(A)2210	REINFORCING STEEL		LB	1,590.000	1.90000	3,021.00		_
1160	511(B)2310	EPOXY COATED REINFORCING STEEL		TB	200,210.000	1.70000	340,357.00		٦
1170	513(B)4300	CLASS B BRIDGE DECK REPAIR		SY	67.000	380.00000	25,460.00		Γ
1180	513(C)4400	CLASS C BRIDGE DECK REPAIR		SY	67.000	00000.009	40,200.00		7
1190	514(A)5210	PILES, FURNISHED (HP 10X42)		LF	310.000	55.00000	17,050.00		



Page 9 of 12

Project ID: 3644804 Federal Project Number: 36448(04)

Project Description: 23rd STREET (193rd E. AVE.)

Line #	Ref. ID	Description	Alt. Set	Alt. Member l	Units	Qty.	Price	Ext. Amount	Fund Package ID	Flags*
1200	514(B)5310	PILES, DRIVEN (HP 10X42)		4	IL.	310.000	21.00000	6,510.00		_
1210	514(L)6300	PILE SPLICE, H-PILE (NON- BIDDABLE)		Э	EA	1.000	200.00000	200.00		Ч
1220	515(A)7200	WATER REPELLENT (VISUALLY INSPECTED)		SY		1,199.000	5.50000	6,594.50		_
1230	516(A)8240	DRILLED SHAFTS 60" DIAMETER		4	IL.	72.000	1,400.00000	100,800.00		_
1240	516(A)8250	DRILLED SHAFTS 72" DIAMETER		5	IL.	36.000	1,400.00000	50,400.00		_
1250	516(C)8400	CROSSHOLE SONIC LOGGING		EA	∢	4.000	2,500.00000	10,000.00		_
1260	517 9110	ELASTOMERIC COATING		SF	L	846.000	25.00000	21,150.00		_
1270	523(A)3200	SEALER CRACK PREPARATION		5	IL.	551.700	3.90000	2,151.63		_
1280	523(B)3300	SEALER RESIN		ڻ ن	GAL	7.200	70.0000	504.00		٦
1290	601(B)1230	TYPE I-A PLAIN RIPRAP		Ĭ	NOT	2,640.000	55.00000	145,200.00		7
1300	601(C)1310	TYPE I-A FILTER BLANKET		Ĭ	NOT	000:509	45.00000	27,225.00		_
1310	613(H)6205	6" PERFORATED PIPE UNDERDRAIN ROUND		H	ш	132.000	38.00000	5,016.00		_
1320	613(1)6310	6" NON-PERF.PIPE UNDERDRAIN RND.		H	Ш	40.000	42.00000	1,680.00		_
1330	619(D)6700	REMOVAL OF EXISTING BRIDGE STRUCTURE		81	RSUM	1.000	75,000.00000	75,000.00		L B

Category Total: \$2,592,087.63

TRAFFIC SIGNING AND STRIPING

Category 0310

GNING AND STRIPING Alternate Set

Alternate Member

Funding Source(s) and Participation: Multiple Fund Packages exist for the Category. See other Funding reports for details.



Page 10 of 12

Federal Project Number: 36448(04) **Project ID: 3644804**

Project Description: 23rd STREET (193rd E. AVE.)

##	e Ref. ID	Description	Alt. Set	Alt. Member	Units	Qty.	Price	Fund Ext. Amount Package ID Flags*	Fund Package ID	Flags*
	Fed Work Class:	Class:								
	Fed Construction Class:	lass:						Category Length: 0	h: 0	
	Category Work Class.	.936						Category Width: 0	h: 0	

Category Work Class:

_	_	_	_	_	
0	0	0	0	0	0
2,170.00	3,822.00	1,496.00	17,540.0	7,280.0	\$32,308.00
155.00000	42.00000	11.00000	1.25000	260.00000	Total:
14.000	91.000	136.000	14,032.000	28.000	Category Total:
EA	SF	님	4	EA	
(PL)REMOVAL OF EXISTING SIGNS	SHEET ALUMINUM SIGNS	2" SQUARE TUBE POST	TRAFFIC STRIPE(PLASTIC)(4" WIDE)	TRAFFIC STRIPE(PLASTIC)(ARROWS)	
805(A)3252	850(A)1200	851(C)2415	855(A)7200	855(B)7304	
1340	1350	1360	1370	1380	

Alternate Member Alternate Set TRAFFIC CONTROL Category 0340 Funding Source(s) and Participation: Multiple Fund Packages exist for the Category. See other Funding reports for details.

Fed Work Class:

Category Work Class:

Category Length: 0 Category Width: 0 Fed Construction Class:

_		LB
38,800.50	12,933.50	220,000.00
1.50000	0.50000	220,000.00000
25,867.000	25,867.000	1.000
L	<u></u>	FSUM
REMOVABLE PAVEMENT MARKING TAPE(4" WIDE)	PAVEMENT MRKNG. REMOVAL(TRAF.STRP)	CONSTRUCTION TRAFFIC CONTROL
1390 857(C)9400	1400 857(F)9700	1410 880(J)7110
1390	1400	1410



Page 11 of 12

Project ID: 3644804 Federal Project Number: 36448(04)

Project Description: 23rd STREET (193rd E. AVE.)

	Flags*
Fund	Package ID
	Ext. Amount
	Price
	Qty.
	Units
Alt.	Member
Alt.	Set
	Description
	Ref. ID
ne	#

Category Total: \$271,734.00

Alternate Member Alternate Set STAKING Category 0600 Funding Source(s) and Participation: Multiple Fund Packages exist for the Category. See other Funding reports for details.

Fed Work Class:

Fed Construction Class:

Category Work Class:

Category Width: 0

Category Length: 0

LΒ 70,000.00 \$70,000.00 70,000.00000 Category Total: 1.000 LSUM CONSTRUCTION STAKING LEVEL II 642(B)3300 1420

Alternate Member Alternate Set CONSTRUCTION Category 0640 Funding Source(s) and Participation: Multiple Fund Packages exist for the Category. See other Funding reports for details.

Fed Work Class:

Category Width: 0 Category Length: 0 Fed Construction Class:

Category Work Class:

L B	LB
15,000.00	444,058.67
15,000.00000	444,058.67000
1.000	1.000
RSUM	LSUM
SWPPP DOCUMENTATION AND MANAGEMENT	MOBILIZATION
220 1100	1440 641 2110
1430	1440

Category Total: \$459,058.67



Page 12 of 12

Project ID: 3644804 Federal Project Number: 36448(04)

Project Description: 23rd STREET (193rd E. AVE.)

	Flags*
Fund	Package ID
	Ext. Amount
	Price
	Qty.
	Units
Alt.	Member
Alt.	Set
	Description
	Ref. ID
Line	#

Estimate Total 3644804

\$9,920,525.30

* Flags: (F)ixed Price, (N)on Bid, (L)ow Cost Contributor, (B)id as Lump Sum

Page 1 of 1



Detail Estimate Funding Summary

Project ID: 3644804

Project Description: 23rd STREET (193rd E. AVE.)

Funding	Amount
	Fund
Funding	Package
	Total
E&C	Amount
E&C	Percent
	Cost
	Category



Page 1	
Detail Estimate Funding Summary By Fund	

	Detail Estimate Funding Summary By Fund	Page 1 of 1
Project ID: 3644804	Project Description: 23rd STREET (193rd E. AVE.)	
	E&C	Funding
Fund ID Category ID	Cost Amount	Total Amount



Detail Estimate Funding Summary By Unit	844804 Project Description : 23rd STREET (193rd E. AVE.)
	Project ID: 3644804

Funding Amount

Total

E&C Amount

Cost

Unit

SURVEY CONTROL DATA

Horizontal Control:
1. Horizontal Control for this survey are based on the Oklahoma State Plane Coordinate System, North Zone - NAD 83 Datum.

, CITY OF

2. Accuracy - 3rd Order

Vertical Controls:
3. Level Datum is Mean Sea Level (USC&GS) NAVD 88

4. The Linear Unit is U.S. Survey Foot.

5. Permanent Benchmark - ADS 10

UTILITY CONTACTS	
CITY OF BROKEN ARROW, OKLAHOMA	CITY OF BROKEN ARROW, OKLAHOMA
ROGER HUGHES P.E.	ROCKY HENKEL, STREET/STORMWATER
485 N. POPLAR. AVE	485 N. POPLAR. AVE
BROKEN ARROW, OKLAHOMA 74012	BROKEN ARROW, OKLAHOMA 74012
(918) 259-7000 X5414	(918) 259-7000 X7380
(918) 259-8453 (FAX)	(918) 251-3383 (FAX)
CITY OF BROKEN ARROW, OKLAHOMA	AT&T (COMMUNICATIONS)
CHARLES VOKES, WATER & SEWER	WAYNE GROOM, TECHNOLOGY OPERATIONS
485 N. POPLAR. AVE	509 S DETROIT AVE, 9TH FLOOR
BROKEN ARROW, OKLAHOMA 74012	TULSA, OK 74120
(918) 259-7000 X7375	(918) 527-7309
OKLAHOMA NATURAL GAS (GASLINE)	COX (COMMUNICATIONS)
STEVE BOLIN, GOVERNMENT RELOCATIONS	CHRIS LONG, RIGHT-OF-WAY AGENT I
5848 E. 15TH ST.	11811 E 515T ST
TULSA, OK 74112	TULSA, OK 74146
(918) 831-8389	(918) 286-4665
PHILLIPS 66 (GASLINE)	WATER - RURAL WATER DISTRICT #4
MATTHEW R. DOWDELL, REAL ESTATE SERVICES AGENT	RYAN SMITH, P.E., PROJECT MANAGER
1388-04 PHILLIPS BUILDING	POE & ASSOCIATES, INC.
420 SOUTH KEELER	4606 S. GARNETT ROAD, SUITE 600
BARTLESVILLE, OK 74003-6670	TULSA, OK 74146
(918) 977-6600	(918) 665-8800
(918) 977-2202 (FAX)	(918) 665-6076 (FAX)
VERIZON (COMMUNICATIONS)	MBO (COMMUNICATIONS)
LESTER RUTHERFORD	JOHNNY ALEXANDER
(918) 809-2359	(918) 550-3433
PSO (ELECTRIC)	CENTURYLINK (COMMUNICATIONS)
LONNY HICKS, TECHNICIAN PRIN	MARK LANE
5223 S GARNETT	(918) 240-7376
TULSA, OK 74146-5902	
(918) 250-6211	

SYMBOL LEGEND

EXISTING SANITARY SEWER LINE EXISTING STORM DRAIN LINE EXISTING TELEPHONE RISER EXISTING FIBER OPTIC LINE Ģ

EXISTING COMMUNICATIONS BOX **EXISTING ELECTRICAL RISER**

EXISTING OVERHEAD ELECTRICAL LINE EXISTING ELECTRICAL TRANSFORMER

EXISTING NATURAL GAS LINE **EXISTING WATER LINE**

EXISTING PAVEMENT EDGE

EXISTING CONCRETE JOINT EXISTING PROPERTY LINE **EXISTING R/W**

EXISTING EASEMENT EXISTING PARCEL EXISTING FENCE

EXISTING FLOWLINE EXISTING SIGN

4

TE TE

PROJECT LOCATION

EXISTING WATER METER EXISTING WATER VALVE 0 ю 🖫


18,280 50 MPH 1,125 4.0% н Max Vertical Grade **DESIGN DATA** Design Speed Min. Hor. R AADT (2018)

0.4% 96 П 11 11

Min. Vertical Grade Min. Vert. K (Sag) Min. Vert. K (Crest)

N. 23rd STREET Where opportunity lives N. 23rd STREET WIDENING FROM ALBANY ST. TO OMAHA S AND BRIDGE REPLACEMENT PROJECT NUMBER ST1931 & ST1932 EXISTING NBI # 19345; NEW NBI # 32731 LOCATION MAP	TULSA CO. WAGGNER CO.	E. OMANA ST. PROJECT LOCATION S. S
---	------------------------	--





INCOG - AADT ESTIMATES (STREETLIGHT DATA), USED IN SECTION A.1

NBI No.:		<u>ıre No.:</u>	Local ID:		Suff. R	•	F0			
19345	72N4070I	E0640003	3			7.50	FO			
Bridge Description.	<u>IFICATION</u>		Type	Insp. Req		<u>ECTION</u> Freq. Insp. D	Date <u>Next Insp.</u>			
39-52-39ft. CONTINUOUS PLATE GIF	DER SPANS		NBI:	_	1 24	months 2/3/20	02/03/2025			
Ollahama I		00DD 0T	FC:	N N	0 0	NA NA				
	acility Carried : eat. Intersect:		UW: OS:	N N	0	NA NA				
3. County: TULSA	9. Location:	193RD E .3S OF 51ST S	- 55.			FICATION				
4. City: BROKEN ARROW	11. Mile Post:	9.712 mi	12.Base	Hwy Net.: No	ot on Base Network	 	No bridge exists			
Admin Area: Unknown 5a. On/Under: Route On Structure	13. LRS Inv.	/ Sub Rte: / 36° 05' 09.29"	20. Toll F	acility: C	n free road	102. Traffic Dir.:	2-way traffic			
5b. Kind of Hwy: City Street	16. Latitude: 17. Longitude:		1	odian: City		103. Temp. Str.:	Not Applicable (P)			
5c. Lvl of Srvc: Mainline	98. Border Bro		22. Owne	-	7 Rural Mir Collecto	104. Hwy System:				
5d. Route No.: 07245	% Responsible		26. Function Class: 07 Rural Mjr Collecto 105. Fed Land Hwy: N/A (NBI) 37. Historical Sig.: Not eligible for NRHP 110. Defense Hwy: Not a STRAHNET I							
5e. Dir. Sufx: N/A (NBI)		lg #: Unknown	100. Def.	Hwy: Not a	a STRAHNET hwy	112. NBIS Length:	Long Enough			
STRUCTURE TY		<u>RIALS</u> Stringer/Girder				DITION				
43a/b. Main Span: 44a/b. Appr. Span:	,	Not Applicable (P)		6 Satisfac rt: N/A (NBI	`		Sub:5 Fair			
45. # of Main Spans: 3		(·)	1	e Notes) 61.Chan./C	than. Prot.: 6 Ban	k Slumping			
46. # of Appr. Spans:					Top of Rail, West sid	de, South to North				
107. Deck Type: Concrete-Ca	st-in-Place				, , , , , , , , , , , , , , , , , , , ,					
108a. Wearing Surface: Bituminous 108b. Membrane: None					LOAD RATING	G AND POSTING				
108b. Membrane: None 108c. Deck protection: None			31. Desig	gn Load: N	/IS 18 (HS 20)	Date Rate	ed: 03/31/2021			
Toda Dask protestion	ND SERVICE		41 Post	- 10.10.01	Posted for load	<u> </u>	<u>. </u>			
19. Detour Length: 4.0 mi	<u>VD SERVICE</u> I 106. Year Red	ennst :	70. Posti 63.Op / 6	ng: ∠ 35.Inv. Rating	? 20.0-29.9%below ı Meth.: 1 LF Lo	oad Factor / 1	LF Load Factor			
27. Year Built: 1977	109. Truck AD				н	HS 3-3	EV3 SHV			
28a/b. Lanes on/und: 2 / 0			64. Oper	ating Rating	` '	33.00 55.00	30.00 38.00			
29. ADT: 12,532 30. Year of ADT: 2020			66. Inver	ntory Rating (tons): 15.00	20.00 33.00	18.00			
42a/b. Type of Svc on/und: Highway	· ,	Waterway				RAISAL				
,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	ETRIC DATA		→ 36a. Brdg 36b. Trar	9	Meets Standards Substandard	68. Deck Geom.:	3 Intolerable - Correct ndclr: Not applicable (N			
10. Vert. Clearance: 99.99 ft	50a. Curb/Sdv	vlk Width L: 1.33 ft	36c. App	_	Substandard	71 Waterway Ade	eq: 6 Equal Minimum			
32. Appr Rwy Width: 26.00 ft	50b. Curb/Sdv			r.Rail Ends:	0 Substandard	72. Appr. Alignme	nt: 5 Above Tolerable			
33. Median: No median	51 Width Curl		67 Str E	valuation:	4 Minimum Tolerab	113. Scour Critica	II: 8 Stable Above Footi			
34. Skew: 45.00° 35. Struct. Flared: No flare	52. Width Out Deck Area					MPROVEMENTS				
47Horizontal Clr: 31.00 ft	53. Min.Vert.C		94. Bridg		\$368,000		31 Repl-Load Capacity			
48. Length Max Span: 52.00 ft	54a.Min.Vt.Un		: 95. Road	lway Cost: Cost	\$203,000 \$589,000	76. Lngth of Impro	8,214			
49. Struct. Length: 132.50 ft	54b. Min. Vert 55a. Min.Lat.U		07 Vr of	Cost Est.:	2015	115. Yr.of Future	ADT: 2040			
	55a. Will.Lat.Ur					TION DATA				
	56 Min Lat Ur		38. Nav.	Control: Clearance:	Permit Not Required 0.0 ft	l ┇ 111. Pier Protect.:	1 Not Required			
200c. Temperature: 41	OKLAHOMA	A ITEMS		Clearance:	0.0 ft	116 Lift Bridge Ve	· .			
200d. Weather: Clear		 	0.70			·				
201. Struc.Stl. ASTM Desig.:	-1 / -1	214a. Posted Weight Limit: b. Posted Speed Limit:	252525 NR		244. Span Length	s: 39 5	52 39			
202. Waterprf.Membrane: -1 Date Installed: 01/01/190	1	c. Narrow/1way Brdg Sign:	No		045 000 000	3.08				
203. Type Exp. Device:		d. Vertical Clr. Sign:	No		245. Girder Depth 246a. Type of Ove		lay			
		Adv. Warning Sign: e. Navigation Lights?:	No No		b. Overlay Thick	ness: 6.00				
204. Type of Railing: SFP-1 205. Material Quantity: -1.00		Working/Not Working:	No		c. Overlay Date: d. Ovly Depth C		006			
208a. Type of Abutment: Skeleton			ICOG		247 Protective Sy					
b. Type of Found.: Steel Pilin 209. Type of Pier/Found.: 2	g / No	218. Functionally Obsolete : 220. Bridge Redecked	FO							
	Drilled Shaft	221 Substr Cond (U/W):	_							
210. Foundation Elev.: -1.00	-1.00	222. Fill Over RCB:			248. # Field Splice					
-1.00 -1.00	-1.00	223. Appr.Slab/Rwy Cond.:	2 od Lood 3 C	ant Suntain	249. Scour Crit. Po 250. Headwall:	UA EXISTS?:	_			
211. Wear.Surf.Prot.Sys: None Date Installed: 01/01/190	1	225. Paint Type/Ovrct: R N/	ed Lead 3 C 'A	Jai System	258. Plans w/Four	nd.in ODOT File:	_			
211c. Silane Reapplied	•		977		259. Scour Eval. ii		_			
211d. Date :			lver		263. Interchange a 264. Interstate Mil		_ -1.00			
213. Utilities Attached: Natural Gas		233. Deck Forming: 238. School Bus Rte.: C	urrent bus ro	ute		•				
<u> </u>			sphalt/Bitumi							
<u> </u>			.00 / 4							
ı		-			•					

Oklahoma Dept. of Transportation - Bridge Inspection Report

NBI No.: Structure No.: Local ID: Suff. Rating: FO 19345 72N4070E0640003 3 47.50 Richard Kingery Contact Into Skrigery Location: Garver LLC Contact Into Skrigery (Contact Into: RSkrigery (@CarverUSA.com Date: 2023.04.24 14.03:37-05'00' 2/3/23 Rick Kingery Inspection Date: Invoice No.: 21T03080-11 Inspected With: Jacob Hoak

BRIDGE NOTES:

Spans numbered South to North. Beams numbered West to East. Bearing numbered West to East. Stringers numbered South to North.

INSPECTION NOTES: 2/3

- PX CLEAN AND PAINT ALL BEAMS.
- PX GUARDRAIL DAMAGE AND ROTTEN TIMBER POSTS AT ALL CORNERS.
- PX REPAIR/SPLICE WEST PILE AT SOUTH ABUTMENT AND ENCASE ALL ABUTMENT PILES.

ELEMENT CONDITION STATE DATA

Elem. / Er	Description	Unit	Total Qty	% 1	Qty. 1	% 2	Qty. 2	% 3	Qty. 3	% 4	Qty. 4	
12 / 4	Re Concrete Deck	sq.ft	4,590.00	0%	0.00	100%	4,590.00	0%	0.00	0%	0.00	
	Covered by asphalt overlay.		,				,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,				_	
	Sutter line has approximately 6 in. of dirt a	nd grave	I.									
510 / 4	Wearing Surfaces	sq.ft	4,590.00	0%	0.00	85%	3,905.00	15%	685.00	0%	0.00	
	Transverse and longitudinal cracking		Iz	-							_	
	South and North joints have cracking	•		nt ie wore	a with higgs	ar enall/on	ening in Nort	hhound l	ane			
	Wearing with exposed aggregate.	and Spain	ng. South joi	iii is woisi	e with bigge	si spaii/op	ening in Non	.iibouiiu i	anc.			
107 / 4	Steel Opn Girder/Beam	ft	480.00	0%	0.00	100%	480.00	0%	0.00	0%	0.00	
	FX - DIAPHRAGM AT BOTH PIERS HAV	E MODE					100.00	070	0.00	070	0.00	
	PX - BEAMS 1 & 4 HAVE PACK RUST AN					V LOSS.						
	PX - ALL STRINGERS OVER PIER 1 ANI					SS WITH	HEAVY RUS	ST THRO	NICHOLIT			
	Pitting (1/16 in.) at bottom of web and bott					OO WIIII	TILAVITIO)	,0011001.			
	nitial section loss and corrosion at Beam		or Dealli Te	and + at i	IGI Z.							
	op and bottom flanges of Beam 1 at Pier		ack rust and	section lo	ee							
	Diaphragm between Beams 3 & 4 over Pie	•			33.							
515 / 4	Steel Protective Coating	sq.ft	6,240.00	0%	0.00	100%	6,240.00	0%	0.00	0%	0.00	
	80% effective.	<u> </u>	,				,			1.5		
210 / 4	Re Conc Pier Wall	ft	40.00	83%	33.00	15%	6.00	3%	1.00	0%	0.00	
	Minor spalls with exposed rebar in both Pi		10.00	0070	- 00.00	1070	0.00	070	. 1.00	070	0.00	
	Pier 2 has a minor 18 in. long vertical crac		and									
215 / 4	Re Conc Abutment	ft	72.00	90%	65.00	10%	7.00	0%	0.00	0%	0.00	
	Ainor staining on both abutments.		12.00	0070	_ 00.00	1070	1.00	070	. 0.00	070	0.00	
	Ainor horizontal crack in West end of Nort	h Abutmo	nt									
	Ainor scaling in North Abutment.	II Abutine	;;;i.									
225 / 4	Steel Pile	(EA)	7.00	0%	0.00	86%	6.00	14%	1.00	0%	0.00	
	PX - PILE NO. 1 OF SOUTH ABUTMENT	· ·						1470	1.00	070	0.00	
	South abutment has 5 exposed piles.	11/10 010	INII IOANI O	LOTION	1000 (007)) AND CO	JININOOIOIN.					
	North abutment has 2 exposed piles.											
	Surface rust throughout.											
234 / 4	Re Conc Pier Cap	ft	66.00	44%	29.00	26%	17.00	30%	20.00	0%	0.00	
	South face of Pier 1 cap has 2 small spalls	with exp	osed rebar		_							
	South face of Pier 1 has a horizontal crack											
	South face of Pier 2 at East end has a 3 ft		spall with exc	osed reb	ar.							
	North face of the Pier 2 cap has 2 small sp	•										
	Pier 2 at West end has map cracking with		•									
F	Rust staining at the ends of both caps.											
304 / 4	Open Expansion Joint	ft	132.00	0%	0.00	100%	132.00	0%	0.00	0%	0.00	
	Covered with asphalt.					,						
311 / 4	Moveable Bearing	each	12.00	0%	0.00	50%	6.00	50%	6.00	0%	0.00	
	PX - 6 ROLLER BEARINGS (1 ON WEST	END OF	THE NORTH	ABUTM	ENT, 4 ON	THE NO	RTH PIER CA	AP, AND	1 ON SOU	TH ABUTM	MENT) WITH	1
	SECTION LOSS.										,	
Е	Bearings are approximately 1 in. or less o	ut of align	ment towards	s the Sout	th on the So	outh abutr	nent.					
	Southwest abutment bearing plate rusted	-										
	2 bearings at North abutment are rotated t											
313 / 4	Fixed Bearing	each	4.00	0%	0.00	0%	0.00	100%	4.00	0%	0.00	
Е	Bearings 1, 2 & 4 on Pier 1 are rusted with	section I	oss.									
331 / 4	Re Conc Bridge Railing	ft	265.00	88%	232.00	12%	32.00	0%	1.00	0%	0.00	
	Vest rail has minor spalls with exposed re	bar.				,		-				
	Vest rail at South end has a 6 in. by 24 in											
	Ainor vertical cracks in both rails.	•										

Oklahoma Dept. of Transportation - Bridge Inspection Report

<u>NE</u>	<u>Bl No.:</u>	Structure No	<u>:</u>		Local I	cal ID: Suff. Rating:						
1	9345	72N4070E0640	003		3				47.50			FC
859 / 4	Soffit	(EA)	1.00	0%	0.00	100%	1.00	0%	0.00	0%	0.00	
4 in. gas line attached to the East side of the soffit with spalling at all the anchor locations.												
Bay	/ 1.2 over Pier 1 has delamir	nation.										
Spa	all in Span 1.											
Sat	uration and scaling around j	oints.										
865 / 4	St.Open Gird End(5Ft (LF)	40.00	0%	0.00	40%	16.00	60%	24.00	0%	0.00	
Initi	ial surface corrosion at all be	am ends.										
Bea	am 1 & 4 over both piers hav	e heavy corrosion wit	h minor se	ction loss.								
870 / 4	Concrete Wingwa	II (EA)	4.00	100%	4.00	0%	0.00	0%	0.00	0%	0.00	
Sou	uthwest wing has a vertical c	rack.										
963 / 4	Steel Section Loss	SF (EA)	1.00	0%	0.00	0%	0.00	100%	1.00	0%	0.00	
PX	- BEARINGS WITH MINOR	SECTION LOSS AT	PIERS 1 A	ND 2 AND	ВОТН АВ	UTMENTS	. 2 DIAPH	RAGMS A	BOVE BO	TH PIERS	RUSTING	WITH
SE	CTION LOSS.											
PX	- SIGNIFICANT SECTION L	OSS AND CORROS	ION AT PII	E NO. 1 O	F SOUTH	ABUTMEN	NT. LOCAL	SECTION	LOSS (35	5%) OF FL	ANGE.	
Exp	oosed piles with minor sectio	n loss at both abutme	ents.									
966 / 4	Exposed Abut.Piling	\ / /	1.00	0%	0.00	100%	1.00	0%	0.00	0%	0.00	
PX	- SOUTH ABUTMENT HAS	5 EXPOSED PILES	(APPROX.	15 IN.) NO	RTH ABU		AS 2 EXPC	SED PILES	S (APPRO	X. 6 IN.)		
968 / 4	Erosion SF	(EA)	1.00	0%	0.00	100%	1.00	0%	0.00	0%	0.00	
PX	- EROSION IS EXPOSING	5 PILES AT SOUTH	ABUTMEN	T AND 2 PI	LES AT N	IORTH ABI	JTMENT.					

Oklahoma Dept. of Transportation - Bridge Channel Report

<u>NBI No.:</u> 19345000000000	Structure No. 72N4070E0640	o.:		<u>L</u> .	ocal ID:		o. Date /2023			
Bridge Description:				38.1	lav. Control:	Permit Not R	equired			
39-52-39ft. CONTINUOUS PLATE GIRD	ER SPANS			39. N	39. Nav. Vert. Clearance: 0.0 ft					
				40. N	lav. Horiz. Clearance:	0.0 ft				
1. State: Oklahoma	1 1	23RD ST		42. 8	Service Type Under:	Waterway				
2. Division: Division 8		CREEK		61. 0	Channel/Chan. Prot.:	6 Bank Slum	ping			
3. County: TULSA		193RD E .3S OF	51ST S	71. V	Vaterway Adeq.:	6 Equal Minimum				
4. City: BROKEN ARROW		36° 05' 09.29"		111.	Pier Protect.:	1 Not Requir				
	17. Longitude:	095° 45' 42.51"		113.	Scour Critical:	8 Stable Abo	ve Footing			
Flowline Note			Scour Crit. POA Exists?:	=						
Flowline, taken from Top of Rail, West si	de, South to North	259.	Scour Eval.in ODOT File?	_						
	Navigable Waterway?	Ur	nkno [.]							
	Type Bedding Material a	t the								
	Bottom of Piers, Piles, S	pread -1								
	Footing or Drilled Shaft: Contributing Drain Area:	-1								
	Drainage Area:	-1								
	High Water Elevation:	-1	.00							
	Low Point Elevation:	-1	.00							
i212 Hydraulic Data:	Top of Opening Elevation:	-1	.00							
	Computed High Water:	-1								
	Stream Velocity Plans):	-1								
	Total Scour for Q100:									
	Total Scour for Overtoppin	g:								
	V - Velocity Downstream:	-1								
	Q - Flow Thru Bridge:	-1								
	Waterway Below Low Stee	el: -1 								
		Channel Profile	<u>Measuremen</u>	<u>ts</u>		_				
256. Measurements were taken from which	ch side of bridge?	pstream Dis	tance from beg	inning of brid	ge to baseline (up to 999.9 t	ft.):	156.0			
1 2	3 4	5	6	7	8	9	10			
Distance from baseline:										
39.00	5.00 91.00	127.00								
Profile:										
10.50 19.00 2	2.00 20.50	9.60								
Event:										
Abutment Pier Flo	owline Pier	Abutment	_	1		_	_			
11 12	13 14	15	16	17	18	19	20			
Distance from baseline:										
Profile:										
Et.										
Event:				1						
		_								

NBI NO.: 19345

STRUCTURE NO.: 72N4070E0640003

COUNTY: TULSA



PHOTO 1: SOUTH
APPROACH WITH 25 TON
POSTING SIGNS
(LOOKING NORTH)




PHOTO 2: NORTH
APPROACH WITH 25 TON
POSTING SIGNS
(LOOKING SOUTH)


NBI NO.: 19345

STRUCTURE NO.: 72N4070E0640003

COUNTY: TULSA









NBI NO.: 19345

STRUCTURE NO.: 72N4070E0640003

COUNTY: TULSA

FACILITY CARRIED: 23RD ST.

FACILITY INTERSECTED: CREEK



PHOTO 5: CHANNEL, DOWNSTREAM (LOOKING EAST)



PHOTO 6: RAIL DAMAGE (TYPICAL)

NBI NO.: 19345

STRUCTURE NO.: 72N4070E0640003

COUNTY: TULSA





PHOTO 8: DECK WITH POTHOLES AND CRACKING IN OVERLAY



NBI NO.: 19345

STRUCTURE NO.: 72N4070E0640003

COUNTY: TULSA



PHOTO 9: BEAM 1 -MINOR SECTION LOSS OF BOTTOM FLANGE AT NORTH ABUTMENT



PHOTO 10: NORTH ABUTMENT - EROSION WITH EXPOSED PILES

NBI NO.: 19345

STRUCTURE NO.: 72N4070E0640003

COUNTY: TULSA

FACILITY CARRIED: 23RD ST.

FACILITY INTERSECTED: CREEK



PHOTO 11: DIAPHRAGMS AT PIER 2 HAVE 100% SECTION LOSS (TYPICAL)



PHOTO 12: BEAM 4 AT PIER 2 – 15% SECTION LOSS

NBI NO.: 19345

STRUCTURE NO.: 72N4070E0640003

COUNTY: TULSA






PHOTO 14: MINOR SPALLS IN SOFFIT AT DRAINS (TYPICAL)



NBI NO.: 19345

STRUCTURE NO.: 72N4070E0640003

COUNTY: TULSA



PHOTO 15: DIAPHRAGMS AT PIER 1 HAVE MODERATE TO HEAVY SECTION LOSS (TYPICAL)




PHOTO 16: BEAM 4 AT PIER 1 – MINOR SECTION LOSS

NBI NO.: 19345

STRUCTURE NO.: 72N4070E0640003

COUNTY: TULSA








PHOTO 18: BEARINGS AT ABUTMENTS HAVE HEAVY CORROSION (TYPICAL)

NBI NO.: 19345

STRUCTURE NO.: 72N4070E0640003

COUNTY: TULSA

FACILITY CARRIED: 23RD ST.

FACILITY INTERSECTED: CREEK



PHOTO 19: PILE 1 SOUTH ABUTMENT FLANGE **RUSTED THROUGH WTH** 35% SECTION LOSS



PHOTO 20: PIER 1 MINOR SPALL AND **DELAMINATION SOUTH** FACE (TYP)

NBI NO.: 19345

STRUCTURE NO.: 72N4070E0640003

COUNTY: TULSA





PHOTO 22: BEARING 4 AT PIER 1



NBI NO.: 19345


STRUCTURE NO.: 72N4070E0640003

COUNTY: TULSA

FACILITY CARRIED: 23RD ST.
FACILITY INTERSECTED: CREEK

INSPECTED BY: Bridge2_Garver INSPECTION DATE: 02/03/2023

LOCATION: -95.7618393691152, 36.08502099396132



Esri, NASA, NGA, USGS, FEMA | City of Tulsa, Missouri Dept. ... Powered by Esri



LOCATION NOTES

Summary of Maintenance Bridge Inspection for City of Broken Arrow February 2023	Facility Feature Scour POA? Existing Load New Load Carried Intersected Posting Posting	R.C.BOX E ROCKFORD CREEK FX: ADD RIPRAP TO MITIGATE 12 IN. SCOUR AT SOUTH END; NO UNDERMINING. * PX: REMOVE SILT AND VEGETATION AT SOUTH SIDE OF CELL 2.	EWED LYNN LANE CREEK FX: NONE (9TH ST.) PX: REMOVE SILT AND DEBRIS FROM ALL CELLS. *	TE 23RD ST. CREEK ES TONS FX: NONE PX: CLEAN AND PAINT ALL BEAMS, DIAPHRAGMS AND BEARINGS. REPAIR/SPLICE WEST PILE AT SOUTH ABUTMENT AND ENCASE ALL ARITMENT PILES REPLACE ALL GILARDRAIL #	ASPEN ST. CREEK CELLS. * PX: NONE	M4060 CREEK 26 TONS FX: REPAIR FENCE ON EAST SIDE.	INDIANWOOD HAIKEY CREEK FX: REPAIR SETTLING AND CRACKED APPROACH ROADWAY PAVEMENT. * PX: REMOVE SILT & TREES BLOCKING CELL 3. *
	Description	(12ft14ft12ft.)X 6ft.X 43ft. R.C.BOX E ROCKFORD ST.	3-12ft. X 9ft. X 80ft. LONG SKEWED RCB	19345 39-52-39ft. CONTINUOUS PLATE GIRDER SPANS	19675 3-10ft.X 6ft.X 114ft. R.C.BOX	29699 3-9ft. X 5ft. X 82ft. LONG RCB	20055 3-10ft.X 8ft.X 37ft. R.C.BOX
	NO.	21521	29698				
	Local	001	005	003	004	000	900

^{*} RECOMMENDATION NOTED IN PREVIOUS INSPECTION REPORT.



