

SURVEY CONTROL DATA

1. HORIZONTAL CONTROL MONUMENTS
OKLAHOMA STATE PLANE COORDINATE SYSTEM -
LAMBERT NORTH PROJECTION
2. BASIS OF BEARING:
LOCAL GRID BEARING
3. VERTICAL CONTROLS (BM):
NAVD 1988
4. SECTION NUMERICAL DESCRIPTION (S-T-R):
SECTION 32, T-19-N, R-14-E
SECTION 4 & 5 T-18-N R-14-E

BEFORE YOU DIG! CALL OKIE 1-800-522-6543



UTILITIES LOCATION SHOWN ON PLAN AND PROFILE WERE OBTAINED FROM INFORMATION PROVIDED BY UTILITY SYSTEM OWNER IN CONJUNCTION WITH EXISTING PHYSICAL FEATURES VISIBLE AT THE TIME OF THE TOPOGRAPHIC SURVEY. LOCATIONS MUST BE VERIFIED BY THE CONTRACTOR PRIOR TO CONSTRUCTION.

UTILITY CONTACTS


<p>CITY OF BROKEN ARROW, OKLAHOMA CITY ENGINEER, TOM HENDRIX P.E. 485 N. POPLAR AVE BROKEN ARROW, OKLAHOMA 74012 (918) 259-7000 EXT. 5414 (918) 259-8453 (FAX)</p>	<p>CITY OF BROKEN ARROW, OKLAHOMA WATER & SEWER, ANTHONY DANIEL 485 N. POPLAR AVE BROKEN ARROW, OKLAHOMA 74012 (918) 259-7000 X7380 (918) 251-3383 (FAX)</p>
<p>CITY OF BROKEN ARROW, OKLAHOMA STREETS/STORMWATER, STEVE ARANT P.E. 485 N. POPLAR AVE BROKEN ARROW, OKLAHOMA 74012 (918) 259-7000 X7380 (918) 251-3383 (FAX)</p>	<p>OKLAHOMA NATURAL GAS (GOVT RELOCATIONS) ATTN.: JONATHON MEADOWS 5848 EAST 15TH STREET TULSA, OKLAHOMA 74112 (918) 831-8215 (918) 949-5735 (CELL)</p>
<p>COX COMMUNICATIONS ATTN: GARY HAMILTON 11811 E. 51ST STREET TULSA, OK 74146 (918) 286-4666 (918) 286-4018 (FAX)</p>	<p>OKLAHOMA NATURAL GAS (EXISTING CONST.) ATTN: BILL MORGAN P.O. BOX 871 TULSA, OKLAHOMA 74102 (918) 451-3814 (918) 451-0899 (FAX)</p>
<p>WINDSTREAM COMMUNICATION ATTN.: GEORGE WHITE 2300 SOUTH 1ST PLACE BROKEN ARROW, OKLAHOMA 74012 (918) 451-3431 (918) 451-1865 (FAX)</p>	<p>AEP / PSD ATTN: JIM WILSON 5223 S GARNETT TULSA, OK 74149 (918) 599-2912 (918) 247-8466 (FAX)</p>



30" WATER LINE

TULSA WATER CONNECTION AT ALBANY STREET AND OLIVE AVENUE

PROJECT NUMBER WL 1611



PROJECT LOCATION SECTION 5, T-18-N, R-14-E, TULSA COUNTY



Holloway, Updike and Bellen, Inc.
Muskogee - Broken Arrow
CA No. 219 Expires 06/30/2017

CA No. 219 Expires 06/30/2017

CITY OF BROKEN ARROW STANDARD CONSTRUCTION SPECIFICATIONS, AUGUST 19, 1999, SHALL GOVERN ALL CONSTRUCTION AS SUPPLEMENTED BY OKLAHOMA STANDARD SPECIFICATION FOR HIGHWAY CONSTRUCTION, APPROVED BY THE DEPARTMENT OF TRANSPORTATION 2009.

FUNDING SOURCE: BAMA UTILITIES WATER RNC

INDEX OF SHEETS

BROKEN ARROW MUNICIPAL AUTHORITY

CHAIRMAN	CRAIG THURMOND
VICE CHAIRMAN	RICHARD CARTER
MEMBER	MIKE LESTER
MEMBER	SCOTT EUDAY
MEMBER	JOHNNIE PARKS

APPROVED

DATE


MICHAEL L. SPURGEON
CITY MANAGER

RECOMMENDED FOR APPROVAL

DATE _____
JEFF T. BIGBY, P.E., CFM
ACTING DIRECTOR, ENGINEERING & CONSTRUCTION

_____ DATE _____

1000



PROJECT NO WI 1611

WATER LINE NOTES:

- ALL WATER DISTRIBUTION SYSTEMS SHALL BE DESIGNED IN ACCORDANCE WITH THE CURRENT CITY OF BROKEN ARROW ENGINEERING DESIGN CRITERIA MANUAL LAND SUBDIVISION CODE AND CONSTRUCTED IN ACCORDANCE WITH STANDARD CONSTRUCTION SPECIFICATIONS.
- PRIOR TO STARTING CONSTRUCTION THE CONTRACTOR SHALL PARTICIPATE IN A PRE-CONSTRUCTION CONFERENCE WITH THE ENGINEERING AND CONSTRUCTION DEPARTMENT. AT THIS CONFERENCE THE CONTRACTOR SHALL FURNISH CERTIFICATION FROM THE MANUFACTURER/SUPPLIER THAT ALL MATERIALS MEET APPLICABLE SPECIFICATIONS. CERTIFICATIONS SHALL BE SUPPLIED IN FIVE (5) COPIES WITH THREE (3) COPIES STAMPED AND APPROVED, BY THE CITY, RETURNED TO THE CONTRACTOR. MATERIALS SHALL NOT BE INSTALLED UNTIL THEY HAVE BEEN APPROVED BY THE CITY.
- ALL WATER DISTRIBUTION SYSTEM SHALL BE INSPECTED BY THE ENGINEERING AND CONSTRUCTION DEPARTMENT UTILITY INSPECTORS, IN ACCORDANCE WITH THE CITY OF BROKEN ARROW ADMINISTRATIVE REGULATION 11-15.
- DIG THOUGH LOCATOR TAPE WILL BE BURIED 2 FEET ABOVE THE LINE.
- WHEN C-905 PVC IS USED, A NO. 12 COATED COPPER WIRE SHALL BE TAPE TO THE TOP SURFACE OF THE PIPE AND CONNECTED TO EACH FIRE HYDRANT BY ATTACHING TO A BOLT, JUST ABOVE GROUND LEVEL.
- ALL IRON PIPE AND FITTINGS SHALL BE POLYWRAPPED.
- STREET CROSSINGS FOR MAIN LINES TWELVE (12) INCHES AND LARGER, SHALL BE PLACED IN CONDUIT.
- ALL DISTRIBUTION LINES IN CONDUIT AND AT DRAINAGE FEATURE CROSSINGS SHALL BE CONSTRUCTED WITH RESTRAINED JOINTS.
- BEDDING, BACKFILL AND COMPACTION OVER WATER LINES SHALL BE IN ACCORDANCE WITH STANDARD DRAWING W01.
- SERVICE LINES SHALL BE TAPPED TO MAIN LINES USING SOLID BRASS SADDLES.
- SERVICE LINES SHALL BE SEAMLESS COPPER WATER TUBE MEETING THE REQUIREMENTS OF ASTM-BBB.
- ALL SERVICE LINE FITTINGS SHALL BE BRASS WITH FLARED, COMPRESSION, SOLDERED OR THREADED CONNECTIONS.
- WHEN CONDUIT IS PROVIDED FOR SERVICE LINES IT SHALL BE SCHEDULE 40 PVC OR STRONGER.
- FIRE HYDRANTS**
 - FIRE HYDRANTS SHALL BE MUELLER CENTURION OR AN APPROVED EQUAL.
 - EACH HYDRANT SHALL BE SET WITH THE STREAMER NOZZLE FACING THE STREET AND WITH A MINIMUM CLEARANCE OF EIGHTEEN INCHES ABOVE THE FINISHED GRADE.
 - ALL EXPOSED PORTIONS OF FIRE HYDRANTS SHALL BE PAINTED WITH A BRIGHT RED ENAMEL AS MANUFACTURED BY GLIDDEN OR DUPONT.
- WHEN WORKING IN OR ADJACENT TO EXISTING SUBDIVISIONS ONLY ONE (1) DAYS WORTH OF TRENCH MAY BE OPEN AT A GIVEN TIME, THIS REQUIREMENT MAY BE MODIFIED, IN WRITING BY THE CONTRACT ADMINISTRATOR, FOR A SPECIFIC PROJECT.
- ROAD CLOSURES MUST BE COORDINATED A MINIMUM OF TWENTY FOUR (24) HOURS IN ADVANCE. ROADS WILL NOT BE CLOSED FOR OVER EIGHT (8) HOURS WITHOUT WRITTEN PERMISSION FROM THE STREET AND STORMWATER DIRECTOR.
- IN ACCORDANCE WITH OAC 252:626-19-2(C) PROVIDE THE WATER LINE WITH A MINIMUM OF 36 INCHES OF COVER WITH SUFFICIENT INSULATION TO PREVENT FREEZING.
- IN ACCORDANCE WITH OAC 252:626-19-2(E), TEST THE INSTALLED PIPE FOR LEAKAGE IN ACCORDANCE WITH AWWA STANDARD SPECIFICATIONS. LEAKAGE MUST NOT EXCEED 10 GAL/INCH DIAMETER PER MILE OF PIPE PER 24 HOURS AT 150 PSI TESTING PRESSURE.
- IN ACCORDANCE WITH OAC 252:626-19-2(F), DISINFECT ALL WATER LINES ACCORDING TO AWWA STANDARD SPECIFICATIONS. OBTAIN SAFE BACTERIOLOGICAL SAMPLES ON TWO CONSECUTIVE DAYS BEFORE PLACING THE WATERLINE INTO SERVICE.
- IN ACCORDANCE WITH OAC 252:626-19-2(H) MAINTAIN THE FOLLOWING MINIMUM SEPARATION DISTANCES BETWEEN WATER LINES AND OTHER UTILITIES.
 - TEN FEET HORIZONTALLY AND TWO FEET VERTICALLY FROM SEWER LINES. WHEN IT IS IMPOSSIBLE TO OBTAIN SUCH HORIZONTAL SEPARATION BETWEEN THE WATER AND SEWER LINES, CONSTRUCT THE SEWER LINE OF WATER PIPE AND PRESSURE TEST IT TO ASSURE TIGHTNESS.
 - FIVE FEET HORIZONTALLY FROM EXISTING OR PROPOSED STORM SEWERS, RAW WATER LINES, PETROLEUM PRODUCT LINES, NATURAL GAS LINES AND OTHER BURIED UTILITY LINES.
 - LOCATE CAST IRON WATER LINES AT LEAST 10 FEET FROM ANY GASOLINE STORAGE TANKS AND PVC WATER LINES AT LEAST 50 FEET HORIZONTALLY FROM ANY GASOLINE STORAGE TANKS AND LINES.
 - FIFTEEN FEET FROM ALL PARTS OF SEPTIC TANKS, ADSORPTION FIELDS OR OTHER SEWAGE TREATMENT AND DISPOSAL SYSTEMS.
- WATER WILL BE PROVIDED VIA THE NEAREST CITY OF BROKEN ARROW HYDRANT AT NO COST TO THE CONTRACTOR. THE CONTRACTOR WILL BE RESPONSIBLE TO OBTAIN A CONSTRUCTION METER FROM THE CITY, PAYING \$1200.00 (ONE THOUSAND, TWO HUNDRED) ESCROW DEPOSIT FOR USE OF THE METER. THE ESCROW MONEY WILL BE RETURNED TO THE CONTRACTOR WHEN THE CONSTRUCTION METER IS RETURNED. FAILURE TO RETURN THE METER WITHIN 2 WORKING DAYS AFTER THE CONTRACT ADMINISTRATOR DETERMINES THE METER IS NO LONGER REQUIRED ON THE PROJECT, COULD RESULT IN WATER CHARGES AND LOSS OF SOME OR ALL OF THE ESCROW DEPOSIT AND CONTRACTOR EARNINGS WITHHELD. CONTRACTOR IS RESPONSIBLE FOR ANY DAMAGES TO METER OR HYDRANT HE MAY CAUSE. CONTRACTOR IS RESPONSIBLE FOR TRANSPORT AND DISTRIBUTION OF WATER AS NEEDED. IF WATER IS OBTAINED FROM ANOTHER ENTITY THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING PERMITS, FEES AND ALL OTHER INCIDENTALS FROM THE ENTITY.

PAY QUANTITY NOTES

- TO BE USED AT ENGINEER'S DIRECTION DOES NOT INCLUDE METER VAULT SUBGRADE.
- UNIT PRICE BID TO INCLUDE COST OF TEMPORARY SEDIMENT REMOVAL AND RESTORATION ON ERODED SLOPES.
- SOLID SLAB SODDING SHALL BE U3, BERMUDA, PRICE BID SHALL INCLUDE FERTILIZING (10-20-10) AT THE RATE OF 100 LB. PER ACRE OF SODDING.
- UNIT PRICE BID SHALL INCLUDE REMOVAL AND DISPOSAL OF TREES AND ALL OTHER DEBRIS NOT INCLUDED IN OTHER ITEMS OF WORK.
- THIS ITEM INCLUDES BORE OF STREETS AND UTILITIES. UNIT PRICE INCLUDES SPACERS, VENTS AND SEALS.
- REFER TO METER VAULT DRAWING FOR LIMITS OF WORK TO INCLUDE IN THIS LUMP SUM BID ITEM.
- UNIT PRICE BID SHALL INCLUDE EXCAVATION BEDDING, BACKFILLING, Dewatering, Seeding and ALL INCIDENTALS.
- UNIT PRICE BID SHALL INCLUDE POLY-WRAPPING DUCTILE IRON PIPE AND FITTINGS.
- INSTALL PER ODOT STANDARD DRAWING TSD-2
- 22.5° BENDS SHALL BE INSTALLED AT DIRECTION OF ENGINEER TO ADJUST ELEVATION IF REQUIRED. BENDS ARE NOT SHOWN ON PLANS.
- PLAIN CONCRETE USED FOR THRUST BLOCKING SHALL BE INSTALLED AS DIRECTED BY ENGINEER IF NECESSARY.
- CONSTRUCTION ALLOWANCE FOR UNFORESEEN WORK NOT INCLUDED IN CONTRACT DOCUMENTS. ALLOWANCE MAY ONLY BE UTILIZED WITH PRIOR WRITTEN APPROVAL OF OWNER.

PAY QUANTITIES				
ITEM	SPEC NO.	DESCRIPTION	UNIT	QUANTITY
1.	BA204-03	Class A Aggregate Base (Trench Stabilization)(1)	CY	50
2.	BA221(B)	Temporary Silt Dike (2) (9)	LF	120
3.	BA221(C)	Temporary Silt Fence (2)	LF	350
4.	BA230(A)	Solid Slab Sodding (3)	SY	2,600
5.	BA310ROW	Clearing (4)	SF	24,000
6.	BA314	Bored Street Crossing (42" Steel Casing 0.50" Wall) (5)	LF	120
7.	BA314	Bored Street Crossing (48" Steel Casing 0.50" Wall) (5)	LF	80
8.	BA330(C)	Plain Concrete (Thrust Blocking) (2500 psi) (11)	CY	15
9.	BA401	30" PVC C905 DR21 (7)	LF	240
10.	BA402	30" DIP CLASS 51 (7) (B)	LF	140
11.	BA402	24" PVC C905 DR18 (7)	LF	10
12.	BA410(A1)	30° 90° BEND (7) (8)	EA	2
13.	BA410(A2)	30° 22.5° BEND (7) (8) (10)	EA	2
14.	BA410(B1)	30° TEE (7) (8)	EA	3
15.	BA410(D1)	24" SLEEVE (7) (8)	EA	2
16.	BA410(G1)	30"x24" REDUCER (7) (8)	EA	2
17.	BA410(G2)	30" MJ CAP (7) (8)	EA	2
18.	BA420(A1)	30" BUTTERFLY VALVE (7) (B)	EA	3
19.	SPECIAL	METER VAULT COMPLETE (6)	LS	1
20.	SPECIAL	CONSTRUCTION ALLOWANCE (12)	ALLOW	1

GENERAL NOTES


- ALL PIPE, VALVES AND FITTINGS SHALL UTILIZE RESTRAINED JOINTS. COSTS FOR RESTRAINED JOINTS SHALL BE INCLUDED IN RESPECTIVE BID ITEMS. RESTRAINED JOINTS SHALL BE AMERICAN "FAST GRIP", U.S. PIPE "FIELD LOK 350" OR APPROVED EQUAL
- ALL GASKETS SHALL BE CERTIFIED AS SUITABLE FOR USE WITH CHLORAMINATED POTABLE WATER.
- ALL FASTENERS SHALL BE TYPE 304 SS ASTM A320/A320M, GRADE 8B BOLTS AND ASTM A194/A194M GRADE 8 NUTS. THIS APPLIES TO ALL BURIED AND IN-VAULT FITTINGS.

TMUA CONTACTS

CALVIN WILLIAMS	MANAGER OF WATER DISTRIBUTION EAST YARD	918-596-8152
RYAN MCKASKLE, P.E.	LEAD ENGINEER WATER DESIGN	918-596-9566
ANTHONY WILKINS, P.E.	Sr. SPECIAL PROJECTS ENGINEER, WATER	918-596-2412



30" WATER LINE
TULSA WATER CONNECTION
AT ALBANY ST AND OLIVE AVE

NOTES & QUANTITIES





PROFILE SCALE: DESIGN DATE DRAFTED DATE
HORZ. LST JME 4/16
VERT. REVIEWED DATE APPROVED DATE
DRAWING NAME: SHEET 2 PROJECT NO.
PLAN OF 8 WL. 1611

STANDARD ABBREVIATIONS				MISCELLANEOUS SYMBOLS AND ABBREVIATIONS								PIPE FITTINGS AND PLUMBING ITEMS																															
AC	ASBESTOS CEMENT PIPE	LS	LUMP SUM	SYMBOL 021 S 12	ABBREV. PF	DESCRIPTION PARSHALL FLUME	SYMBOL	DESCRIPTION FENCE	DOUBLE LINE	SINGLE LINE	DESCRIPTION WELDED JOINT	ABBREV.																															
ASP	ASPHALT	LT	LEFT	Ⓜ	LL	LINE LABELS	—	SECTION LINE	—	—	GROOVED END JOINT																																
AWWA	AMERICAN WATER WORKS ASSOC.	MAX	MAXIMUM	Ⓜ	FM	FLOW METER	—P—	PROPERTY LINE	—	—	BELL & SPIGOT JOINT																																
BM	BENCH MARK - ELEVATION	MIN	MINIMUM	Ⓜ	GV	GATE VALVE	∅	POWER POLE	—	—	FLANGED COUPLING ADAPTER																																
CI	CAST IRON INLET	MJ	MECHANICAL JOINT PIPE FITTING	Ⓜ	BFV	BUTTERFLY VALVE	♪	TRAFFIC SIGN	—	—	WITH THRUST TIES																																
C-C	CENTER TO CENTER	MSL	MEAN SEA LEVEL	Ⓜ	BV	BALL VALVE	✳	LIGHT POLE	—	—	FLEXIBLE COUPLING	FLW. CPLG.																															
CFS	CUBIC FEET PER SECOND	O.C.	ON CENTER	Ⓜ	BCV	BALL CHECK VALVE	—700—	PROPOSED CONTOUR	—	—	FLX. COUPLING WITH THRUST TIES																																
CIP	CAST IRON PIPE	OD	OUTSIDE DIAMETER	Ⓜ	CV	CHECK VALVE	—	EXIST. CONTOUR	—	—	ELASTOMETER BELLows EXP. JOINT	EXP. JT.																															
CL	CENTER LINE	ODEQ	OK. DEPT. OF ENV. QUALITY	Ⓜ	PV	PLUG VALVE	○○○	TREES	—	—	ELBOW UP	ELL																															
CMP	CORRUGATED METAL PIPE	ODOT	OK. DEPT. OF TRANSPORTATION	Ⓜ	PRV	PRESSURE RELIEF VALVE	—	Q SWALE & FLOW	—	—	ELBOW DOWN	ELL																															
CMPA	CORRUGATED METAL PIPE - ARCH	PE	POLYETHYLENE PIPE	Ⓜ	PCV	PRESSURE CONTROL VALVE	—	CREEK OR DITCH SWALE	—	—	ELBOW 90 DEGREE	ELL																															
CONC	CONCRETE	PL	PROPERTY LINE	Ⓜ	VALVE w/ MECHANICAL OPERATOR	—	DRIVES & MINOR ROADS	—	—	ELBOW 45 DEGREE	ELL																																
CP	SURVEY CONTROL POINT	PP	POWER POLE	—	DV	DIAPHRAGM VALVE	—	RAILROAD	—	—	LATERAL																																
CPVC	CHLORINATED POLYVINYL CHLORIDE PIPE	PSI	POUNDS PER SQUARE INCH	—	BFP	BACK FLOW PREVENTER	—	EXIST. RIGHT OF WAY	—	—	TEE	TEE																															
CY	CUBIC YARD	PVC	POLYVINYL CHLORIDE PIPE	—	ARV	AIR RELIEF VALVE	△	REFERENCE POINT	—	—	TEE UP	TEE																															
D/E	DRAINAGE EASEMENT	Q100	100 YR FLOW	—	SW	STRUCTURE WALL	▲ B-3	BORING LOCATION	—	—	TEE DOWN	TEE																															
DIP	DUCTILE IRON PIPE	RCB	REINFORCED CONCRETE BOX	—	ES	EXISTING STRUCTURE	—	SURVEY BASE LINE	—	—	CROSS	CROSS																															
EA	EACH	RCP	REINFORCED CONCRETE PIPE	—	B	BLOWER	—	PROPOSED LINE	—	—	Y-STRAINER	YS																															
EL	ELEVATION	RJ	RESTRAINED JOINT - PIPE	—	P	PUMPS	—	CONDUIT	—	—	COUPLING	CPLG.																															
E-W	EACH WAY	RT	RIGHT	—	MV	MUD VALVE	—	IRON PIN	—	—	LATERAL UP																																
FG	FINISHED GROUND ELEVATION	RW	RIGHT OF WAY LINE	—	FC	FLEXIBLE COUPLING	—	EXISTING TREE LINE	—	—	LATERAL DOWN																																
FH	FIRE HYDRANT	SS	SANITARY SEWER	—	FC	FLEXIBLE METAL COUPLING	—	PROPOSED CLEARING LIMIT	—	—	CONCENTRIC REDUCER	CONC. RED.																															
FL	FLOW LINE	STA	STATION	—	SAMPLER	—	PIPING (TO BE ABANDONED)	—	—	ECCENTRIC REDUCER	ECC. RED.																																
FM	FORCE MAIN (SEWER)	STM	STORM SEWER LINE	—	TV	TELESCOPIC VALVE	—	MATCHLINE	—	—	UN																																
GV	GATE VALVE	SY	SQUARE YARD	—	MOTOR OPERATOR	—	SECTION NUMBER OR DETAIL LETTER	—	—	FLANGED JOINT	FLG																																
HW	HEADWALL	TYP	TYPICAL	—	PRESSURE GAUGE	—	—	—	—	FLANGED COUPLING ADAPTER	FCA																																
HYD	FIRE HYDRANT	U/E	UTILITY EASEMENT	—	TEMPERATURE GAUGE	—	—	—	—	MECHANICAL JOINT	MJ																																
ID	INSIDE DIAMETER	WL	WATER LINE	—	SA	SURFACE AERATOR	—	—	—	—	MJ w/ RETAINER GLAND	RJ																															
IP	IRON PIN			—	PT	PRESSURE TRANSDUCER	—	—	—	—																																	
LF	LINEAL FEET			—	BF	BLIND FLANGE	—	—	—	—																																	
<u>SURVEY SYMBOLS</u>				—	—	HOSE CONNECTION	—	—	—	—																																	
<u>FLOW STREAM IDENTIFICATION</u>				—	—	“Y” TYPE STRAINER	—	—	—	—																																	
				—	—	EXPANSION JOINT	—	—	—	—																																	
				—	—	AIR RELEASE VALVE	—	—	—	—																																	
<u>EXISTING UTILITY LINE SYMBOLS</u>																																											
				SYMBOL	DESCRIPTION																																						
				WL	WATER LINE																																						
				SS	SANITARY SEWER LINE																																						
				STM	STORM SEWER																																						
				UGE	UNDERGROUND ELECTRIC																																						
				GAS	GAS LINE																																						
				OHE	OVERHEAD ELECTRIC																																						
				TUG	UNDERGROUND TELEPHONE																																						
				FOC	FIBER OPTIC CABLE																																						
				PL	PROPERTY LINE																																						
				FM	SANITARY SEWER FORCE MAIN																																						
DATE	REVISIONS																																										
30" WATER LINE TULSA WATER CONNECTION AT ALBANY ST AND OLIVE AVE																																											
LEGEND AND SYMBOLS																																											
PROFILE SCALE: HORZ. <input type="text"/>	DESIGN LST	DATE JME	DRAFTED 4/16	VERT. <input type="text"/>	REVIEWED DATE	APPROVED DATE																																					
DRAWING NAME: PLAN	SHEET OF	3 8	PROJECT NO. WL 1611																																								




DATE	REVISIONS	BROKEN ARROW Municipal Authority	PROFILE SCALE: HORZ. _____ VERT. _____	DESIGN DATE LST JME REVIEWED DATE APPROVED DATE	DRAFTED DATE 4/16
			DRAWING NAME: PLAN SHEET 4 OF 8	PROJECT NO. WL. 1611	



DATE	REVISIONS




BROKEN ARROW
Municipal Authority




30" WATER LINE
TULSA WATER CONNECTION
AT ALBANY ST AND OLIVE AVE

PLAN & PROFILE

PROFILE SCALE:	DESIGN DATE	DRAFTED DATE	DATE
HORZ. 1:20	LST	JME	4/16
VERT. 1:5	REVIEWED DATE	APPROVED DATE	DATE
DRAWING NAME:	5	8	PROJECT NO.
PLAN	OF	8	WL_1611







METER VAULT PLAN
 A 6
 SCALE: 1/2" = 1'-0"

NOTES:

1. ALL COSTS FOR INSTALLATION OF PIPE AND MATERIALS BETWEEN AND INCLUDING 30"x18" REDUCERS SHALL BE INCLUDED IN LUMP SUM COST FOR METER VAULT.
2. ACCESS LADDERS SHALL BE 316 S.S. CONSTRUCTION WITH 316 S.S. HARDWARE. INSTALL PER MANUFACTURERS RECOMMENDATION. CONTRACTOR SHALL PROVIDE AND INSTALL "MILLER SOLL GLIDELOC 304 S.S." FALL PROTECTION SYSTEM ON ALL LADDERS. A TOTAL OF TWO TROLLEYS AND TWO HARNESSSES SHALL BE SUPPLIED BY THE CONTRACTOR FOR THIS PROJECT.






GENERAL CONSTRUCTION NOTES


CORNER AND INTERSECTION REINFORCING DETAILS

1. TYPICAL HORIZONTAL WALL CORNER AND INTERSECTION REINFORCING LAYOUT IS SHOWN TO AVOID CONGESTION AND PERMIT PROPER PLACEMENT. FOR SIZE AND SPACING SEE PLANS. ALL HORIZONTAL REINFORCING AT CORNERS AND INTERSECTIONS SHALL BE FABRICATED AND INSTALLED WITH SPLICES LOCATED WHERE SHOWN REGARDLESS OF BAR SIZE AND SPACING
2. WHERE THE CORNER OR INTERSECTION REINFORCING SIZE AND SPACING IS NOT SHOWN, NOTED OR TABULATED ON THE PLANS, THE SIZE AND SPACING SHALL BE THE SAME AS THE WALL HORIZONTAL REINFORCING SHOWN ON THE WALL SECTIONS OR AS NOTED FOR THE REINFORCING BETWEEN THE CORNERS OR INTERSECTIONS
3. EXCEPT WHERE OTHERWISE SHOWN ON THE DRAWINGS, THE LENGTH INDICATED AS "NOTE 3" SHALL BE THE LESSER OF D/4, 10 FEET, OR 1.0 TIMES THE HEIGHT OF THE WALL, EXCEPT THAT IN NO CASE SHALL IT BE LESS THAN 2.0 FEET
4. D = LENGTH OF WALL PARALLEL TO THE BAR LENGTH IN QUESTION
5. EXCEPT WHERE OTHERWISE SHOWN ON THE DRAWINGS, THE LENGTH INDICATED AS "NOTE 5" SHALL BE EQUAL TO ONE "LAP LENGTH" AS REQUIRED BY THE GENERAL STRUCTURAL NOTES. USE THE LAP LENGTH AS REQUIRED FOR THE SMALLER OF THE TWO REINFORCING BARS BEING SPLICED
6. UNLESS OTHERWISE NOTED, "B" AND "C" BARS ARE THE SAME SIZE AND SPACING AND "F" AND "G" BARS ARE THE SAME SIZE AND SPACING




TYPICAL DOUBLE MAT CORNER AND INTERSECTION REINFORCING

2
21 NTS
(SEE PLANS FOR SIZE AND SPACING)




5
21 NTS
OPENING REINFORCING



NOTES:


1. FOR FORM TIE HOLES ON OUTSIDE FACE OF WALL BELOW GRADE, FILL WITH NONSHRINK GROUT (DRY PACK)
2. THE SPACING OF FORM TIES ON EXPOSED PORTIONS OF WALLS SHALL BE APPROXIMATELY EQUAL HORIZONTALLY AND VERTICALLY AND SHALL BE UNIFORM IN EACH DIRECTION
3. WHERE CHAULKING IS NOT SPECIFIED OR SHOWN, DRY PACK EXTERIOR TIE HOLES WITH NONSHRINK GROUT WITH COLOR OF GROUT TO MATCH COLOR OF CONCRETE AS CLOSE AS POSSIBLE
4. DRY PACK METHOD SHALL BE AS SPECIFIED USING STEEL TOOLS

FORM SNAP TIE-HOLE



TYPICAL SINGLE MAT CORNER AND INTERSECTION REINFORCING

4
21 NTS



THICKNESS OF CONCRETE	BAR SIZE	BAR LENGTH "C"
<12"	4	3'-0"
12" TO 18"	5	3'-0"
>18"	6	3'-8"

TYPICAL EXTRA REINFORCING AT OPENINGS AND HATCHES

6
21 NTS

